



Tipo è la versione a scomparsa della serie Mini Modo LED; è particolarmente adatto per applicazioni nelle controsoffittature di spazi espositivi, vetrine ed appartamenti.

Tipo è un faretto ad incasso completo di 3 LED nelle tonalità bianco caldo 3000K o bianco naturale 4000K con lenti da 15° o 40°. La sua struttura è in lamiera con gruppo ottico orientabile fino ad un max di 30°; dissipatore in alluminio pressofuso. IP20. Alimentabile a 350, 500 e 700 mA, alimentatore escluso.

Trimless version of Mini Modo collection.

Tipo is a recessed spot complete with 3 LED in warm 3000K and natural 4000K white tones with 15° or 40° lenses. Its structure is in sheet metal with 30° adjustable optic group; heat sink in die-cast aluminum included in the lighting fitting. IP20. Powered at 350, 500 and 700mA, driver excluded.

Tipo est la version sans cadre de la collection Mini Modo LED.

Tipo un appareil d'encastrement avec 3 LED teinte blanc chaud 3000K ou blanc naturel 4000K, angles 15° ou 40°. La structure est en tôle avec groupe optique réglable jusqu'à 30°; dissipateur en fonte d'aluminium. IP20. Alimentation à 350, 500 et 700 mA, driver exclu.












JET.5270.157 3 LEDx1,2W/2,4W 350/700mA

Versione quadrata con LED tono bianco naturale 4000K, lenti 40°.
Version with square frame with LED natural white 4000K, 40° lens.
Version avec cadre carré avec LED blanc naturel 4000K, lentilles 40°.


JET.5270.158 3 LEDx1,2W/2,4W 350/700mA

Versione quadrata con LED tono bianco caldo 3000K, lenti 40°.
Version with square frame with LED warm white 3000K, 40° lens.
Version avec cadre carré avec LED blanc chaud 3000K, lentilles 40°.




Driver forniti su richiesta come accessori.
Drivers offered on demand as accessories.
Driver fournis séparément comme accessoires.

Accessori / Accessories / Accessoires




LAA.5100.006

Gruppo lenti a fascio medio (24°).
Group medium beam lens (24°).
Groupe lentilles intensive (24°).




LAA.5100.007

Gruppo lenti a fascio stretto (15°).
Group narrow beam lens (15°).
Groupe lentilles intensive (15°).




AAA.TRSL01

Driver per 1 apparecchio da 3 LED 350mA.
Driver for 1 fitting for 3 LED 350mA.
Driver pour 1 appareil de 3 LED 350mA.




AAA.TRSL31

Driver per 1 apparecchio da 3 LED 700mA.
Driver for 1 fitting for 3 LED 700mA.
Driver pour 1 appareil de 3 LED 700mA.



AAA.TRSL05

Driver per max 3 apparecchi da 3 LED 350mA.
Driver for max 3 3 LED fittings 350mA.
Driver pour max 3 appareils de 3 LED 350mA.



AAA.TRSL35

Driver per max 3 apparecchi da 3 LED 700mA.
Driver for max 3 3 LED fittings 700mA.
Driver pour max 3 appareils de 3 LED 700mA.

