


Adjustable ceiling luminaire for very low voltage halogen lamps (12V).
Coated steel sheet frame.
Power supply: 230V - 50 Hz.
Supplied with electronic transformer.

CODE	DESCRIPTION		Size (mm)
3145	HMG (HALOSPOT111) 75W max - 12V - G53		
3146	MR (CDM-R111) - 70W - GX8.5 230V - 50Hz Colour: 01 - 18 IP 40 Kg 2.55		
3245	HMG (HALOSPOT111) 2 x 75W max - 12V - G53		
3246	MR (CDM-R111) - 2 x 70W - GX8.5 230V - 50Hz Colour: 01 - 18 IP 40 Kg 3.55		
3345	HMG (HALOSPOT111) 3 x 75W max - 12V - G53		
3346	HMG (HALOSPOT111) 2 x 75W max - 12V - G53 MR (CDM-R111) - 70W - GX8.5 230V - 50Hz Colour: 01 - 18 IP 40 Kg 4.40		
3447	HMG (HALOSPOT111) 4 x 75W max - 12V - G53 230V - 50Hz Colour: 01 - 18 IP 40 Kg 5.35		
3448	HMG (HALOSPOT111) 4 x 75W max - 12V - G53 230V - 50Hz Colour: 01 - 18 IP 40 Kg 4.80		



ACCESSORIES

919 High-bay installation kit.
It includes: ceiling rose, power supply cable, steel wires with height adjusting devices

01 white
18 grey
Can be adjusted separately on both axes.

NOTE