

























Adjustable recessed luminaire for very low voltage halogen lamps (12V).
Coated steel sheet frame.
Separate power supply: 12V
Ballast not included.
Type for fluorescent lamps.
White opaline polycarbonate louver.

EXTREME

DESIGN - QUATTROBI TECHNICAL DEPARTMENT

CODE	DESCRIPTION	Size (mm)	
3141 R	HMG (HALOSPOT111) 100W max - 12V - G53	 H-120-H Ø147	
3154 R	MT (CDM-T) - 35/70/150W - G12 Colour: 02 IP 40 Kg 0.95	 H-144-H Ø144-H	
			
			
	Colour: 01 white on request		
3241 R	HMG (HALOSPOT111) 2 x 100W max - 12V - G53	 H-120-H H-143-H 271	
3243 R	MT (CDM-T) - 2x35/70/150W - G12 Colour: 02 IP 40 Kg 1.45	 H-128-H 276 H-143-H	
			
			
	Colour: 01 white on request		
3341 R	HMG (HALOSPOT111) 3 x 100W max - 12V - G53	 H-120-H H-143-H 406	
3343 R	MT (CDM-T) - 3x35/70/150W - G12 Colour: 02 IP 40 Kg 2.00	 H-126-H 408 H-143-H	
			
			
	Colour: 01 white on request		
3142	FSQH (TC-D) - 24W - 2G11 230V - 50Hz Colour: 01 IP 40 Kg 1.45	 H-115-H H-143-H 271	
			
			
	Electronic ballast		
3143	FSQH (TC-D) - 36W - 2G11 230V - 50Hz Colour: 01 IP 40 Kg 2.00	 H-115-H H-143-H 406	
			
			
	Electronic ballast		

ACCESSORIES

799 Lamp frame for installation of CDM-R111 discharge lamps 

01 white
02 black
Can be adjusted separately on both axes.

NOTE