

CE F IP67



2.000Kg




pag 588


**Cassaforma inclusa (cod. A4 CF 120)**

Housing included  
Inklusives Gehäuse  
Contra caja incluida


**L08**



**L20**



**L45**



# A4 L1

Proiettore tondo a LED 3x3W. Ghiera in acciaio inox. Corpo in pressofusione di alluminio verniciato in polveri poliester.

3x3W LED round projector. Stainless steel ring nut. Aluminium pressure die casting body, varnished with polyester powders.

Runder Scheinwerfer mit 3x3W LED. Nutmutter aus Edelstahl. Körper aus Aluminiumspritzguss mit Polyesterlacken lackiert.

Projector redondo de LED 3x3W. Abrazadera de acero inoxidable. Cuerpo de aluminio inyectado fundido a presión pintado con polvo poliéster.

**Apparecchi ad incasso a LED**  
LED recessed appliances  
Einbaugeräte mit LED  
Luminarias para empotrar de LED



# A4 L1

**Potenza assorbita**  
Absorbed power  
Leistungsaufnahme  
Potencia absorbida

**8,4W**

**Tensione in ingresso**  
Input voltage  
Eingangsspannung  
Tensión en entrada

**230V**

**Vita media / ore**  
Average life / hours  
Lebensdauer / Stunden  
Vida media / horas

**50.000**

**Flusso luminoso**  
Luminous flux  
Lichtstrom  
Flujo luminoso

**BI** 540 lm  
**W** 450 lm

**Temperatura di colore**  
Colour temperature  
Farbetemperatur  
Temperatura de color

**BI 5.500 K**  
**W 3.000 K**

**Grado di protezione**  
Protection degree  
Schutzgrad  
Grado de protección

**IP67**

**Temperatura di esercizio**  
Operating temperature  
Betriebstemperatur  
Temperatura de ejercicio

**- 40° C + 50° C**

**Classe di isolamento**  
Insulation class  
Schutzklasse  
Clase de aislamiento

**I**

**Angolo di emissione**  
Emission angle  
Emissionswinkel  
Ángulo de emisión

**L08** 8°  
**L20** 20°  
**L45** 45°

**Resistenza all'urto**  
Shock resistance  
Stoßfestigkeit  
Resistencia al impacto

**IK10**  
carrabile  
suitable for vehicles  
befahrbar  
para tráfico rodado

**Alimentatore incorporato**  
Built-in power supply  
Eingebautes Vorschaltgerät  
Alimentador incorporado

**Finitura**  
Finishing  
Ausführung  
Acabado



**I**  
Acciaio inox  
Stainless steel  
Edelstahl  
Acero inoxidable

**Colori LED**  
LED colours  
LED Farben  
Colores LED



**BI** Bianco  
White  
Weiss  
Blanco  
**W** Warm  
Warm  
Warm  
Warm