

**Cassaforma PMMA**

PMMA housing  
Gehäuse aus PMMA  
Contracaja de PMMA

A4CF35

pag 490



CE F IP68



**Lente piana trasparente**


Transparent flat lens  
Transparente flache Linse  
Lente plana transparente

LPT

**Lente piana sabbiata**

Sanded flat lens  
Sandgestrahlte flache Linse  
Lente plana enarenada

LPS



# A4 R23 S

Apparecchio segnapasso fisso  
quadro 0,4W con guarnizione e  
diffusore satinato.

Fixed square step indicator 0,4W  
with gasket and satinized diffuser.

Unbewegliche quadratische  
Schrittleuchte 0,4W mit Dichtung  
und satiniertem Diffusor.

Luminaria de balizado fijo  
cuadrado 0,4W con junta  
y difusor satinado.

**Apparecchi ad incasso a LED**  
LED recessed appliances  
Einbaugeräte mit LED  
Luminarias para empotrar de LED



# A4 R23 S

**Potenza assorbita**  
Absorbed power  
Leistungsaufnahme  
Potencia absorbida  
**0,4W**

**Tensione di alimentazione**  
Supply voltage  
Netzspannung  
Tensión de alimentación  
**12 V**  
costante  
constant  
konstant  
constant

**Vita media / ore**  
Average life / hours  
Lebensdauer / Stunden  
Vida media / horas  
**100.000**

**Flusso luminoso**  
Luminous flux  
Lichtstrom  
Flujo luminoso  
**15 lm**

**Temperatura di colore**  
Colour temperature  
Farbetemperatur  
Temperatura de color  
**BI** 6.500 K  
**W** 3.000 K

**Grado di protezione**  
Protection degree  
Schutzgrad  
Grado de protección  
**IP68**

**Temperatura di esercizio**  
Operating temperature  
Betriebstemperatur  
Temperatura de ejercicio  
**- 40° C + 50° C**

**Classe di isolamento**  
Insulation class  
Schutzklasse  
Clase de aislamiento  
**III**

**Angolo di emissione**  
Emission angle  
Emissionswinkel  
Ángulo de emisión  
**LPT/LPS 110°**

**Resistenza all'urto**  
Shock resistance  
Stoßfestigkeit  
Resistencia al impacto  
**IK10**  
calpestabile  
applicable on pedestrian areas  
begehbar  
de suelo pisable

**Alimentatori disponibili**  
Available power supplies  
Erhältliche Vorschaltgeräte  
Alimentadores disponibles  
**A4A8-4-12** max 10  
**Apparecchi**  
Appliances  
Geräte  
Luminarias  
**A4A8-20-12** max 50  
**Apparecchi**  
Appliances  
Geräte  
Luminarias

**Dimmer disponibili**  
Available dimmers  
Erhältliche Dimmer  
Dimmer disponibles  
**A4A11-J70-12**  
max 168  
**Apparecchi**  
Appliances  
Geräte  
Luminarias

**Finitura**  
Finishing  
Ausführung  
Acabado



**I**  
Acciaio inox  
Stainless steel  
Edelstahl  
Acero inoxidable

**Colori LED**  
LED colours  
LED Farben  
Colores LED



**BI** Bianco  
White  
Weiss  
Blanco  
**W** Warm  
Warm  
Warm  
Warm