

Cassaforma PMMA





PMMA housing
Gehäuse aus PMMA
Contracaja de PMMA

A4CF35

pag 490



CE F IP68



A4 R2L

Apparecchio fisso tondo 1W con guarnizione, disponibile con lente piana di diverso fascio di apertura.

Round fixed spot 1W with gasket, available with different beam with flat lens.

Unbewegliche runde Spot 1W mit Dichtung. Erhältlich mit flacher Linse mit unterschiedlichem Lichtbündel.

Foco fijo redondo 1W con junta, disponible con lente plana con haz de apertura diferente.



Apparecchi ad incasso a LED
LED recessed appliances
Einbaugeräte mit LED
Luminarias para empotrar de LED

A4 R2L



Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

1,4W

Corrente di alimentazione
Supply current
Stromspannung
Corriente de alimentación

350 mA
costante
constant
konstant
constant

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

80.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

BI 80 lm
W 62 lm

Temperatura di colore
Colour temperature
Farbetemperatur
Temperatura de color

BI 5.500 K
W 3.000 K

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP68

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Angolo di emissione
Emission angle
Emissionswinkel
Angulo de emisión

L10 10°
L20 20°
L45 45°
LET elliptic

Resistenza all'urto
Shock resistance
Stoßfestigkeit
Resistencia al impacto

IK10
calpestabile
applicable on pedestrian areas
begehbar
de suelo pisable

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A1-4
max 4
Apparecchi
Appliances
Geräte
Luminarias

A4A1-10
max 10
Apparecchi
Appliances
Geräte
Luminarias

Dimmer disponibili
Available dimmers
Erhältliche Dimmer
Dimmer disponibles

A4A2-D25
max 24
Apparecchi
Appliances
Geräte
Luminarias

A4A11-J50
DMX max 24
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



I
Acciaio inox
Stainless steel
Edelstahl
Acero inoxidable

Colori LED
LED colours
LED Farben
Colores LED



BI
Bianco
White
Weiss
Blanco

W
Warm
Warm
Warm
Warm

AB
Ambra
Amber
Amber
Ambar

BL
Blu
Blue
Blau
Azul