



Cassaforma PMMA

PMMA housing
Gehäuse aus PMMA
Contracaja de PMMA

A4CF35

pag 490



CE F IP68



A4 R2 S

Apparecchio segnapasso fisso tondo 0,4W con diffusore satinato.

Fixed round step indicator with 0,4W and satinized diffuser.

Unbewegliche runde Schrittleuchte mit 0,4W und satiniertem Diffusor.

Luminaria de balizado fija redonda 0,4W con difusor satinado.



Apparecchi ad incasso a LED
LED recessed appliances
Einbaugeräte mit LED
Luminarias para empotrar de LED

A4 R2 S



Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

0,4W

Tensione di alimentazione
Supply voltage
Netzspannung
Tensión de alimentación

12 V
costante
constant
konstant
constant

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

100.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

15 lm

Temperatura di colore
Colour temperature
Farbetemperatur
Temperatura de color

BI 6.500 K
W 3.000 K

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP68

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Angolo di emissione
Emission angle
Emissionswinkel
Ángulo de emisión

LPT/LPS 110°

Resistenza all'urto
Shock resistance
Stoßfestigkeit
Resistencia al impacto

IK10
calpestabile
applicable on pedestrian areas
begehbar
de suelo pisable

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A8-4-12 max 10
Apparecchi
Appliances
Geräte
Luminarias

A4A8-20-12 max 50
Apparecchi
Appliances
Geräte
Luminarias

Dimmer disponibili
Available dimmers
Erhältliche Dimmer
Dimmer disponibles

A4A11-J70-12 max 168
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



I
Acciaio inox
Stainless steel
Edelstahl
Acero inoxidable

Colori LED
LED colours
LED Farben
Colores LED



BI Bianco
White
Weiss
Blanco

W Warm
Warm
Warm
Warm