



CE  IP40  78 mm



L45



A4 F3 AD CR

Apparecchio tondo orientabile 3x3W
Solaring Light con molle.

Adjustable round spot 3x3W Solaring
Light with springs.

Bewegliche runde Spot 3x3W
Solaring Light mit Federungen.

Foco redondo orientable 3x3W
Solaring Light con muelles.

Apparecchi ad incasso a LED
LED recessed appliances
Einbaugeräte mit LED
Luminarias para empotrar de LED

3



A4 F3 AD CR

Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

8,4W

Corrente di alimentazione
Supply current
Stromspannung
Corriente de alimentación

700 mA
costante
constant
konstant
constant

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

50.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

480 lm

Temperatura di colore
Colour temperature
Farbetemperatur
Temperatura de color

2.500 K
4.000 K
8.500 K

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP40

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Angolo di emissione
Emission angle
Emissionswinkel
Ángulo de emisión

L45 45°

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A11-JP
dimmer max 12
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



N
Nichel opaco
Matt nickel
Nickel matt
Níquel opaco

C
Cromo
Chrome
Chrom
Cromo

BO
Bianco
White
Weiss
Blanco

Colori LED
LED colours
LED Farben
Colores LED



CR