

Cassaforma PMMA

PMMA housing
Gehäuse aus PMMA
Contracaja de PMMA

A4CF42

pag 490



CE F IP68



4 bar

12 Volt



Lente convessa trasparente

Transparent convex lens
Transparente konvexe Linse
Lente convexe transparente

LCT

Lente piana trasparente

Transparent flat lens
Transparente flache Linse
Lente plana transparente

LPT

Lente convessa sabbiata



Sanded convex lens
Sandgestrahlte konvexe Linse
Lente convexe enarenada

LCS

Lente piana sabbiata

Sanded flat lens
Sandgestrahlte flache Linse
Lente plana enarenada

LPS



A4 R13

Apparecchio ad immersione IP68 in acciaio inox, con vetro temperato trasparente e guarnizione in silicone, sorgente luminosa a LED 3W.

Immersion IP68 stainless steel appliance with transparent tempered glass and silicon gasket, luminous source with 3W LED.

Unterwassergerät aus Edelstahl IP68, mit durchsichtigem temperiertem Glas und Silikondichtung, Leuchtquelle mit 3W LEDs.

Luminaria de inmersión de acero inoxidable IP68, con vidrio templado transparente y junta de silicona, fuente de luz de LED 3W.

Apparecchi ad incasso a LED
LED recessed appliances
Einbaugeräte mit LED
Luminarias para empotrar de LED



A4 R13

Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

2,8W

Corrente di alimentazione
Supply current
Stromspannung
Corriente de alimentación

700 mA
costante
constant
konstant
constant

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

80.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

BI 192 lm
W 144 lm

Temperatura di colore
Colour temperature
Farbetemperatur
Temperatura de color

BI 5.500 K
W 3.000 K

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP68

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Angolo di emissione
Emission angle
Emissionswinkel
Angulo de emisión

LCT/LCS 60°
LPT/LPS 110°

Resistenza all'urto
Shock resistance
Stoßfestigkeit
Resistencia al impacto

IK10
calpestabile
applicable on pedestrian areas
begehbar
de suelo pisable

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A2-3
max 3
Apparecchi
Appliances
Geräte
Luminarias

Dimmer disponibili
Available dimmers
Erhältliche Dimmer
Dimmer disponibles

A4A11-JP12
DMX max 12
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



I
Acciaio inox
Stainless steel
Edelstahl
Acero inoxidable

Colori LED
LED colours
LED Farben
Colores LED



BI
Bianco
White
Weiss
Blanco

W
Warm
Warm
Warm
Warm