



CE  IP44  35 mm



TIME 40 RGB

Apparecchio con diffusore in PMMA ad emissione laterale del fascio luminoso.

Appliance with PMMA diffuser, side emission of the light beam.

Gerät mit PMMA-Diffusor und seitlicher Lichtbündelabgabe.

Luminaria con difusor en PMMA de emisión lateral del haz luminoso.



Apparecchi a soffitto e parete
Ceiling and wall appliances
Decken- und Wandgeräte
Luminarias de techo y de pared

4



TIME 40 RGB

Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

R 1W
G 1,3W
B 1,3W

Corrente di alimentazione
Supply current
Stromspannung
Corriente de alimentación

350 mA
costante
constant
konstant
constante

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

80.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

R 30 lm
G 50 lm
B 14 lm

Lunghezza d'onda
Wave length
Wellenlänge
Longitud de onda

R 630 nm
G 525 nm
B 470 nm

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP44

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Emissione
Emission
Emission
Emisión

Laterale
Lateral
Seitlich
Lateral

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A11-EJ
max 8
Apparecchi
Appliances
Geräte
Luminarias

A4A11-J50
DMX max 6
Apparecchi
Appliances
Geräte
Luminarias

A4A11-JP
DMX max 12
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



N
Nichel opaco
Matt nickel
Nickel matt
Níquel opaco

Colori LED
LED colours
LED Farben
Colores LED



RGB