



CE  IP44  59 mm



TIME 70

Apparecchio con diffusore in PMMA ad emissione laterale del fascio luminoso.

Appliance with PMMA diffuser, side emission of the light beam.

Gerät mit PMMA-Diffusor und seitlicher Lichtbündelabgabe.

Luminaria con difusor en PMMA de emisión lateral del haz luminoso.



Apparecchi a soffitto e parete
Ceiling and wall appliances
Decken- und Wandgeräte
Luminarias de techo y de pared

4



TIME 70

Potenza assorbita
Absorbed power
Leistungsaufnahme
Potencia absorbida

4,9W

Corrente di alimentazione
Supply current
Stromspannung
Corriente de alimentación

700 mA
costante
constant
konstant
constante

Vita media / ore
Average life / hours
Lebensdauer / Stunden
Vida media / horas

50.000

Flusso luminoso
Luminous flux
Lichtstrom
Flujo luminoso

BI 300 lm
W 253 lm

Temperatura di colore
Colour temperature
Farbetemperatur
Temperatura de color

BI 5.500 K
W 3.000 K

Grado di protezione
Protection degree
Schutzgrad
Grado de protección

IP44

Temperatura di esercizio
Operating temperature
Betriebstemperatur
Temperatura de ejercicio

- 40° C + 50° C

Classe di isolamento
Insulation class
Schutzklasse
Clase de aislamiento

III

Emissione
Emission
Emission
Emisión

Laterale
Lateral
Seitlich
Lateral

Alimentatori disponibili
Available power supplies
Erhältliche Vorschaltgeräte
Alimentadores disponibles

A4A2-7 max 4
Apparecchi
Appliances
Geräte
Luminarias

A4A2-9 max 5
Apparecchi
Appliances
Geräte
Luminarias

Dimmer disponibili
Available dimmers
Erhältliche Dimmer
Dimmer disponibles

A4A2-D25 max 5
Apparecchi
Appliances
Geräte
Luminarias

A4A11-JP DMX max 28
Apparecchi
Appliances
Geräte
Luminarias

Finitura
Finishing
Ausführung
Acabado



N
Nichel opaco
Matt nickel
Nickel matt
Níquel opaco

Colori LED
LED colours
LED Farben
Colores LED



BI
Bianco
White
Weiss
Blanco



W
Warm
Warm
Warm
Warm