



CE  IP20  75 mm



# TIME 90 RGB

Apparecchio con diffusore in PMMA ad emissione laterale del fascio luminoso.

Appliance with PMMA diffuser, side emission of the light beam.

Gerät mit PMMA-Diffusor und seitlicher Lichtbündelabgabe.

Luminaria con difusor en PMMA de emisión lateral del haz luminoso.



**Apparecchi a soffitto e parete**  
Ceiling and wall appliances  
Decken- und Wandgeräte  
Luminarias de techo y de pared

4



# TIME 90 RGB

**Potenza assorbita**  
Absorbed power  
Leistungsaufnahme  
Potencia absorbida

**R** 3W  
**G** 3,9W  
**B** 3,9W

**Corrente di alimentazione**  
Supply current  
Stromspannung  
Corriente de alimentación

**350 mA**  
costante  
constant  
konstant  
constante

**Vita media / ore**  
Average life / hours  
Lebensdauer / Stunden  
Vida media / horas

**50.000**

**Flusso luminoso**  
Luminous flux  
Lichtstrom  
Flujo luminoso

**R** 90 lm  
**G** 150 lm  
**B** 42 lm

**Lunghezza d'onda**  
Wave length  
Wellenlänge  
Longitud de onda

**R** 630 nm  
**G** 525 nm  
**B** 470 nm

**Grado di protezione**  
Protection degree  
Schutzgrad  
Grado de protección

**IP20**

**Temperatura di esercizio**  
Operating temperature  
Betriebstemperatur  
Temperatura de ejercicio

**- 40° C + 50° C**

**Classe di isolamento**  
Insulation class  
Schutzklasse  
Clase de aislamiento

**III**

**Emissione**  
Emission  
Emission  
Emisión

**Laterale**  
Lateral  
Seitlich  
Lateral

**Alimentatori disponibili**  
Available power supplies  
Erhältliche Vorschaltgeräte  
Alimentadores disponibles

**A4A11-EJ**  
max 2  
**Apparecchi**  
Appliances  
Geräte  
Luminarias

**A4A11-J50**  
DMX max 2  
**Apparecchi**  
Appliances  
Geräte  
Luminarias

**A4A11-JP**  
DMX max 4  
**Apparecchi**  
Appliances  
Geräte  
Luminarias

**Finitura**  
Finishing  
Ausführung  
Acabado



**N**  
Nichel opaco  
Matt nickel  
Nickel matt  
Níquel opaco

**Colori LED**  
LED colours  
LED Farben  
Colores LED



**RGB**