




Perseo LED è il nuovo apparecchio d'illuminazione da incasso a pavimento carrabile della famiglia Perseo. Perseo LED è disponibile nella versione a 7 LED con gruppo ottico fisso nelle tonalità bianco caldo 3000K e bianco freddo 5500K con lenti da 15° o 40°. Struttura interamente in acciaio Inox, vetro temperato trasparente, grado di protezione IP67. Cassaforma inclusa. I pozzetti per l'incasso sono identici a quelli dell'esistente modello Perseo. Alimentatore a 350 mA, fornito di serie nell'apparecchio

Perseo LED is the LED development of the drive over outdoor collection Perseo. It is available in 7 LED models with fixed optic, warm white 3000K or cold 4000K white with 15° or 40° lenses. Stainless still body tempered transparent glass, IP67. Recessed box included. The recessed box are the same of the existing Perseo. Driver 350 mA included in the fittings.

Perseo LED est le nouveau appareil d'éclairage à encastrément au sol carrossable de la collection Perseo. Perseo LED est équipé de 7 LED, optique fixe. En teinte blanc chaud 3000K ou blanc froid 4000K, angle 15° ou 40°. Corps entièrement en acier inoxydable, verre trempé transparent. Degré de protection IP67. Boîtier d'encastrément inclus. Les boîtiers pour l'encastrément sont les mêmes du model Perseo déjà existan. Driver 350 mA inclus.



CE IP679



**JEP.010756**







7 LEDx1,2W

Versione con LED bianco freddo 5500K, lenti 40°.  
Driver 350 mA incluso.  
Version with cold white LED 5500K, lenses 40°.  
Driver 350 mA included.  
Version avec LED blanc froid 5500K, lentilles 40°.  
Driver 350 mA inclus.


**JEP.010758**

7 LEDx1,2W

Versione con LED bianco caldo 3000K, lenti 40°.  
Driver 350 mA incluso.  
Version with warm white LED 3000K, lenses 40°.  
Driver 350 mA included.  
Version avec LED blanc chaud 3000K, lentilles 40°.  
Driver 350 mA inclus.




Accessori / Accessories / Accessoires




**LAA.5100.001**  
Lente a fascio medio (24°).  
Medium beam lens (24°).  
Lentilles intensive (24°).

**LAA.5100.002**  
Lente a fascio stretto (15°).  
Narrow beam lens (15°).  
Lentilles intensive (15°).




**JEP.FR2**

Cornice quadrata in acciaio inox, in sostituzione dell'anello standard.  
Stainless steel square frame, as a replacement of the standard ring.  
L'acier sans tache cadre carré, substitution de la bague standard.



**JEP.AG**

Griglia anti abbagliamento.  
Anti glare louver.  
Grille contre l'éblouissement.



**JEP.C3**

○ 09

Calottina di copertura tre finestre.  
Covering dome with three windows.  
Couverture à trois fenêtres.



**JEP.C1**

○ 09

Calottina di copertura a una finestra.  
Covering dome with one window.  
Couverture à une fenêtre.



**JEP.FG**

Vetro sabbato in sostituzione al vetro standard.  
Sanded glass as a replacement of the standard glass.  
Verre sablé en substitution du verre standard.

