


ICARO

- Corpo in materiale termoplastico.
- Resistenza al filo incandescente 700°C.
- Parabola riflettente in alluminio.
- Viti di chiusura in acciaio inox.
- Passacavo in gomma.
- Lampada esclusa.
- Classe I, IP54.

- *Light fitting made of thermoplastic material.*
- *Incandescent wire 700°C.*
- *Aluminium reflector.*
- *Closing screws in stainless steel.*
- *Rubber cable entry.*
- *Lamp not included.*
- *Class I, IP54.*




 .2 Bianco
White.

 .7 Verde
Green.

 .3 Nero
Black.

 .4 Grigio metallizzato
Grey metallized.

 .6 Grigio
Grey.



F.6228

- **A60 100W E27** 
- 1380 lumen
- Classe I - Class I




F.6229

- **A60 75W E27** 
- 960 lumen
- **A60 25W E27** 
- 220 lumen
- Classe I - Class I



F.6230

- **A60 100W E27** 
- 1380 lumen
- Classe II - Class II



- **A60 75W E27** 
960 lumen
- **A60 25W E27** 
220 lumen
- Classe II - *Class II*




F.6231

- **TC-S 9W G23** 
2 x 600 lumen
- Classe I - *Class I*



F.6232

- **TC-S 9W G23** 
2 x 600 lumen
- Classe II - *Class II*



F.6233

- **TC-D 18W G24d-2** 
1200 lumen
- Classe I - *Class I*



F.6234

- **TC-D 26W G24d-3** 
1800 lumen
- Classe I - *Class I*



F.6235

- **FSS-16W GR8** 
1060 lumen
- Classe I - *Class I*



F.6236

- Disponibile anche nella versione in emergenza (durata 1h al 20%) **F.6237**.
- Available in emergency also (duration 1 hour at 20%) **F.6237**.

- **FSS-16W GR8** 
1060 lumen
- Classe II - *Class II*




F.6238

- **FSS-28W GR8** 
2050 lumen
- Classe I - *Class I*



F.6239

- **FSS-28W GR8** 
2050 lumen
- Classe II - *Class II*



F.6240