






SIRIO

- Corpo in materiale termoplastico.
- Resistenza al filo incandescente 700°C.
- Parabola riflettente in alluminio.
- Viti di chiusura in acciaio inox.
- Passacavo in gomma.
- Lampada esclusa.
- Classe I, IP44.


- *Light fitting made of thermoplastic material.*
- *Incandescent wire 700°C.*
- *Aluminium reflector.*
- *Closing screws in stainless steel.*
- *Rubber cable entry.*
- *Lamp not included.*
- *Class I, IP44.*



-  .2 Bianco
White.
-  .3 Nero
Black.
-  .6 Grigio
Grey.
-  .7 Verde
Green.





F.6207

- **A60 100W E27**  1380 lumen
- Classe I - *Class I*




F.6208

- **A60 75W E27**  960 lumen
- **A60 25W E27**  220 lumen
- Classe I - *Class I*



F.6209

- **A60 100W E27**  1380 lumen
- Classe II - *Class II*



- **A60 75W E27** 
960 lumen
- **A60 25W E27** 
220 lumen
- Classe II - *Class II*




F.6210

- **TC-S 9W G23** 
2 x 600 lumen
- Classe I - *Class I*



F.6211

- **TC-S 9W G23** 
2 x 600 lumen
- Classe II - *Class II*



F.6212

- **TC-D 18W G24d-2** 
1200 lumen
- Classe I - *Class I*



F.6213

- **TC-D 26W G24d-3** 
1800 lumen
- Classe I - *Class I*



F.6214

- **FSS-16W GR8** 
1060 lumen
- Classe I - *Class I*



F.6215

- Disponibile anche nella versione in emergenza (durata 1h al 20%) **F.6216.**
- *Available in emergency also (duration 1 hour at 20%) F.6216.*

- **FSS-16W GR8** 
1060 lumen
- Classe II - *Class II*



F.6217

- **FC 22W G10q** 
1350 lumen
- Classe I - *Class I*



F.6218