



TECHNICAL SPECIFICATIONS

RATING:	IP68 Commercial Grade
CABLE:	UV stabilized, Single Circuit
FITTINGS:	Polycarbonate ultra-sonically welded to cable
LENS:	UV stabilised polycarbonate, fade resistant Clear Domes (C) or Coloured Domes (CD)
POWER SUPPLIES:	Regulated Power Supply 12V DC (HRPS)
MOUNTING:	Dependant on application Double sided Velcro Tape available
CABLE COLOUR:	Green Cable (GC) or Clear Cable (CC)
LED COLOUR:	Green (G) White (W) Blue (B) Yellow (Y) Amber (A) Red (R) Warm White (WW)
	0.3Watt p/lamp – 100,00 hour lamp life (dependant on application)
TAIL LENGTH:	Please specify tail length in metres
SPACING:	50mm (050) 100mm (100) 150mm (150) 200mm (200) 250mm (250) 300mm (300)

SPECIFICATION CODE:
HLP – (Spacing Code) – (Cable Colour) – (Lens) – (LED Colour)

PLEASE NOTE This product is also available with incandescent lamps
 This lighting is designed specifically for outdoor applications

DIMENSIONS

HEIGHT:	22mm without cap 27mm with cap
WIDTH:	15.10mm cap width 15.95mm fitting width

CONSTRUCTION MATERIAL

UV Stabilised Cable with ultra sonically welded polycarbonate fittings with lens caps

APPLICATIONS

- Tree lighting
 - Display lighting
 - Garden feature lighting
 - Building lighting
- or similar