



TECHNICAL SPECIFICATIONS

RATING: IP44 (Indoor Use)
HOUSING; Polycarbonate flame retardant tube
LED'S: 100,000 hours (dependant on installation environment)
 12V DC, 0.3Watts per 3 LED's
FINISH: Polycarbonate
MOUNTING: Dependant on application
TUBE COLOUR: Green **(G)** Clear **(C)** Blue **(B)**
 Opaque **(O)** Amber **(A)** Red **(R)**
LED COLOUR: Green **(G)** White **(W)** Blue **(B)**
 Yellow **(Y)** Amber **(A)** Red **(R)**
 Warm White **(WW)**
POWER SUPPLIES: Regulated Power Supply **(HRPS)**
LAMP SPACING: 12.5mm **(012)** 25mm **(025)** 50mm **(050)**
 100mm **(100)** 200mm **(200)**

CONSTRUCTION MATERIAL

Polycarbonate flame retardant tube

SPECIFICATION CODE:

HLT – (Spacing of Lamps) – (Tube Colour) – (LED Colour)

PLEASE NOTE: This lighting tube is designed to suit **Extrusion** series for stairs and wall features.

DIMENSIONS

HEIGHT: 10mm
WIDTH: 10mm
LENGTH: Custom made to length

APPLICATIONS

- Lecture theatres – Stairs, Handrails
- Cinemas – Stairs, Foyers
- Auditoriums – Steps
- Nightclubs – Dance Floors, Entries, Stairs
- Gaming rooms – Wall Displays, Ceiling Displays, or similar