


LASER Exterior Fern Lite

Fern Lite is suited to illumination of low level foliage. Light is emitted on a horizontal plane through a UV stable acrylic lens with anti-glare mesh around 360 degrees. The luminaire uses a 5, 10 or 20 watt halogen bi-pin lamp and does not project any vertical light due to the anti-glare hood.

This luminaire is machined from a choice of 10mm thick aluminium with a UV stable powder coated finish or solid copper.



Ordering Information

Luminaire Type

FN - Fern Lite

Material/Finish

BK - Black
BZ - Bronze
GN - Green
STAR - Silver Star
COP - Copper

Accessories

CJK150 - Cable Joint Kit
/300 - Ground Spike 300mm (12")
For an alternative LED option start at page 10.4

Ordering Example: FN COP - Fern Lite in Copper
FN/300 BK - Fern Lite in Black with
300mm (12") Ground Spike
CJK150 - Cable Joint Kit
(Accessories ordered separately)

Luminaire Construction

Body: high corrosion resistant 63.5mm (2 1/2") x 10mm (25/64") aluminium.
End cap: Solid aluminium 63.5mm (2 1/2") rod.
Spike: 11.11mm (7/16") aluminium rod.
Hood: 140mm (5 1/2") x 1.2mm (1/16") hand spun aluminium.
With chromate substrate and high UV resistant polyester powder coat
Colours: Black, Bronze, Green, Silver Star.
Copper:
Body 63.5mm (2 1/2") x 10mm (13/32"). End cap - solid copper 63.5mm (2 1/2") rod.
Spike: 11.11mm (7/16") copper rod.
Hood: 140mm (5 1/2") x 1.2mm (1/16") hand spun copper.

Mounting

Ground spike 150mm (6") or 300mm (12") directly into the earth.

Features

Lens:
UV stable Polycarbonate with anti-glare mesh.
Anti Glare Hood:
Diameter 140mm (5 1/2"). No upward light or glare projected.
Gasket:
Silicone, iron impregnated 220°C (428°F)
Lamp Holder:
G4 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.
Accessories:
Cable Joint Kit (Cat. CJK150). Not approved for USA/Canada.
Ground Spike 300mm (12") (Cat. /300).