


LASER Exterior Driveway Lite



The Driveway Lite is a luminaire designed to mount flush with the level of the driveway, pathway, hotel floors or building foyer. It has a 'Flush Fit' lens which stops water pooling and depositing dirt on the lens. There is no lip to trip over.

The Driveway Lite is supplied with a mounting canister that facilitates ease of installation. The luminaire can be driven over or walked upon without being damaged. Designed so the lamp can be angled up to 20 degrees, directed at a bush, tree, or the outside of a building, etc. without the need to remove the luminaire from the mounting canister due to the vandal-resistant three allen head screw fixing system which attaches the flange to the body of the luminaire. This luminaire has a solid bronze or 316 stainless steel flange with a powder coated black body.



Ordering Information

Luminaire Type	Flange Option	Body	Accessories
DWL - Driveway Lite	SBZ - Solid Bronze SS - 316 Stainless Steel	Black only	CJK150 - Cable Joint Kit HCR - Hex Cell Louvre STEPLLF - Frosted Lens For an alternative LED option start at page 10.4
<p>Ordering Example: DWL SBZ - Driveway Lite with Solid Bronze Flange.</p> <p>STEPLLF - Frosted Lens (Accessories ordered separately)</p>			

Luminaire Construction

Body:

Cast from virgin high corrosion resistant CC401 low copper aluminium alloy, with chromate substrate and high UV resistant black polyester powder coat.

Flanges:

The flange is attached to the body by three 316 stainless steel allen head anti vandal screws and is available in either

Solid bronze - 150mm (6") bar.

316 Stainless Steel - 150mm (6") rod.

Mounting

Supplied with a mounting canister for casting in concrete to facilitate ease of installation. The luminaire can be driven over or walked upon without being damaged. Maximum drive over speed 10 km/h (6 mph) and weight 1500kg (3300lbs).

Features

Lens:

12mm (1/2") flush fit clear tempered shatter resistant glass.

Life Time Warranty.

Gasket:

Nytrol 220°C (428°F).

Lamp Holder:

GU5.3 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables. Lamp holder can be rotated 360° and angled up to 20 degrees.

Accessories:

Cable Joint Kit (Cat. CJK150).
Not approved for USA/Canada.
Frosted Lens (Cat. STEPLLF).
Hex Cell Louvre (Cat. HCR).