


## LASER Exterior Twin Bar Lite



The Twin Bar Lite is ideal for wall or sign illumination using 2 x 20 watt lamps with an IG40 transformer. The luminaire has two individual spot lites which can be aimed in two entirely different directions. Each lite has a fully adjustable arm allowing 360 degree rotation and 0 - 90 degree elevation adjustment. The heads are mounted on a 250mm (10") bar with twin ground spikes.

This luminaire is machined from a choice of 10mm thick aluminium with a UV stable powder coated finish, solid copper or 316 stainless steel with a clear, tempered, flush glass lens and high temperature silicon gaskets.

### Ordering Information



#### Luminaire Type

TBL - Twin Bar Lite

#### Material/Finish

BK - Black  
BZ - Bronze  
GN - Green  
STAR - Silver Star  
COP - Copper  
SS - 316 Stainless Steel

#### Accessories

CJK150 - Cable Joint Kit  
LENSSTEPF - Frosted Lens  
GG - Glare Guard  
HCL - Hex Cell Louvre Adaptor  
/300 - 300 (12") Spike  
For an alternative LED option start at page 10.4

Ordering Example: TBL COP - Twin Bar Lite in Copper  
TBL /300 BZ - Twin Bar Lite in Bronze with 300mm (12") Spike

HCL BK - Hex Cell Louvre Adaptor in Black  
(Accessories ordered separately)

#### Luminaire Construction

CNC machined from one of the following metals:

High corrosion resistant 63.5mm (2 1/2") x 10mm (25/64") aluminium.  
End cap - solid aluminium 63.5mm (2 1/2") rod, with chromate substrate and high UV resistant polyester powder coat

**Colours** Black, Bronze, Green, Silver Star.

**Copper** 63.5mm (2 1/2") x 10mm (13/32"). End cap - solid copper 63.5mm (2 1/2") rod.

**316 Stainless Steel** 9mm (11/32"). End cap - solid 316 stainless steel 63.5mm (2 1/2") rod.

#### Mounting

Spike 150mm (6") 300mm (12") mounted directly into the ground.

#### Features

**Lens:**  
10mm (3/8") clear 'flush fit' shatter resistant glass. Life Time Warranty.

#### Gaskets:

Silicone, iron impregnated 220°C (428°F).

#### Lamp Holders:

GU5.3 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

#### Accessories:

Cable Joint Kit (Cat. CJK150).  
Not approved for USA/Canada.  
Frosted Lens (Cat. LENSSTEPF).  
Glare Guard (Cat. GG).  
Hex Cell Louvre Adaptor (Cat. HCL).  
Ground Spike 300mm (12") (Cat. /300).

#### Swivels:

Aluminium and Copper luminaires 360° rotation and 0 - 90° elevation, solid brass with anti rust spring.

Stainless Steel luminaires - 360° rotation and 0 - 90° elevation, full stainless steel construction.