




LASER Exterior Wall Down Lite




Wall Down Lite

Cat. No. DL
Cat. No. DL/R
Cat. No. DLGU



Retro™
USA/Canada



GU10

The Wall Down Lite is suitable for mounting on timber, masonry, stone, etc. non-adjustable for one way wall washing, can be mounted with the lamp directed up or down. Water resistant with a 78mm diameter mounting base, complete with stainless steel screws.

The Retro™ is a 110/240-12 ac mains option suited to an installation where mounting a transformer is a problem, e.g. a brick wall where there is only the cable protruding out of the wall and it is not an option to recess the transformer or when replacing an existing light fitting. The base size increases in size to accommodate the encapsulated IP66 dimmable transformer.

A GU10 version of this luminaire is also available and does not require a transformer. However, a longer luminaire body is needed to accommodate the longer lamp.

Ordering Information

Luminaire Type	Material/Finish	Accessories
DL - Wall Down Lite	BK - Black BZ - Bronze GN - Green STAR - Silver Star WH - White WB - Birch DG - Dark Grey OG - Olive Green RG - Beige PR - Primrose COP - Copper SS - 316 Stainless Steel	CJK150 - Cable Joint Kit LENSSTEPF - Frosted Lens GG - Glare Guard HCL - Hex Cell Louvre Adaptor /R - Retro™ Transformer 110/240-12 volt WBAP - Wall Box Adaptor Plate For LED refer to page 10.4
Ordering Example: DL BK - Wall Down Lite in Black DL/R SS - Wall Down Lite Retro™ in 316 Stainless Steel DLGU BK - Wall Down Lite in Black LENSSTEPF - Frosted Lens (Accessories ordered separately)		

Luminaire Construction
CNC machined from the following metals:
Body: High corrosion resistant low copper 63.5mm (2 1/2") x 10mm (25/64") aluminium. End cap - solid aluminium 63.5mm (2 1/2") rod.
Base & Mounting Plate (Retro™): Cast from virgin high corrosion resistant CC401 low copper aluminium alloy chromate substrate and high UV resistant polyester powder coat - Black, Bronze, Green, Silver Star, White, Birch, Dark Grey, Olive Green, Beige, Primrose.
Body: Copper 63.5mm (2 1/2") x 10mm (25/64"). End cap - solid copper 63.5mm (2 1/2") rod.
Base: Copper Hand spun 2mm (5/64")
Mounting Plate: Forged brass (Retro™)
Body: 316 Stainless Steel 63.5mm (2 1/2") x 10mm (25/64") rod. End cap - 316 stainless steel 63.5mm (2 1/2") rod.
Base: Investment cast and CNC machined (Retro™).
Mounting Plate: Investment cast and CNC machined.

Mounting
12 volt: the luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth. A Wall Box Adaptor Plate is available as an accessory to fit 3.0 and 4.0 junction boxes for USA/Canada.
Retro™ 110/240-12 volt: a mounting plate is fixed to the wall using two screws, the luminaire is fitted to the mounting plate.

Features
Lens:
10mm (3/8") clear flush fit shatter resistant glass.
Lifetime Warranty.
Gasket:
Silicone, iron impregnated 220°C (428°F).
Lamp Holder:
GU5.3 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.
GU10 - Refer sheet no.10.9
Accessories:
Cable Joint Kit (Cat. CJK150)
Not approved for USA/Canada.
Frosted Lens (Cat. LENSSTEPF).
Glare Guard (Cat. GG).
Hex Cell Louvre Adaptor (Cat. HCL).
Retro™ transformer 110/240-12 volt (Cat. /R).
Wall Box Adaptor Plate (Cat. WBAP 12 volt luminaire USA / Canada).