



DL 4067 Graham

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4067.2.42.00.1	TC	G23	2 x 11 W BI/WH
	599.4067.2.42.00.2	TC	G23	2 x 11 W NE/BK
	599.4067.2.42.00.3	TC	G23	2 x 11 W GI/GR
	599.4067.2.42.00.4	TC	G23	2 x 11 W AN/AN
	599.4067.2.42.00.0	TC	G23	2 x 11 W AR/SI

DL 4067 Graham

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4067.1.46.00.1	TC-D	G24-d3	1 x 26 W BI/WH
	599.4067.1.46.00.2	TC-D	G24-d3	1 x 26 W NE/BK
	599.4067.1.46.00.3	TC-D	G24-d3	1 x 26 W GI/GR
	599.4067.1.46.00.4	TC-D	G24-d3	1 x 26 W AN/AN
	599.4067.1.46.00.0	TC-D	G24-d3	1 x 26 W AR/SI

DL 4067 Graham

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4067.1.52.00.1	TC-TEL	GX24-q4	1 x 42 W BI/WH
	599.4067.1.52.00.2	TC-TEL	GX24-q4	1 x 42 W NE/BK
	599.4067.1.52.00.3	TC-TEL	GX24-q4	1 x 42 W GI/GR
	599.4067.1.52.00.4	TC-TEL	GX24-q4	1 x 42 W AN/AN
	599.4067.1.52.00.0	TC-TEL	GX24-q4	1 x 42 W AR/SI

DL 4067 Graham

Lampada fluorescente compatta elettronica
Electronic compact fluorescent Lamp

	599.4067.1.54.00.1	TC-TSE	E27	1 x 23 W BI/WH
	599.4067.1.54.00.2	TC-TSE	E27	1 x 23 W NE/BK
	599.4067.1.54.00.3	TC-TSE	E27	1 x 23 W GI/GR
	599.4067.1.54.00.4	TC-TSE	E27	1 x 23 W AN/AN
	599.4067.1.54.00.0	TC-TSE	E27	1 x 23 W AR/SI

599.9032.A.00.00.Z
Base di ancoraggio
Anchor bolt kit

CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
SELF-EXTINGUISHING IMPACT RESISTANT POLYCARBONATE DIFFUSER WITH UV STABILIZED
ADDITIVE
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 4068 Graham

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4068.2.42.00.1	TC	G23	2 x 11 W BI/WH
	599.4068.2.42.00.2	TC	G23	2 x 11 W NE/BK
	599.4068.2.42.00.3	TC	G23	2 x 11 W GI/GR
	599.4068.2.42.00.4	TC	G23	2 x 11 W AN/AN
	599.4068.2.42.00.0	TC	G23	2 x 11 W AR/SI

DL 4068 Graham

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4068.1.46.00.1	TC-D	G24-d3	1 x 26 W BI/WH
	599.4068.1.46.00.2	TC-D	G24-d3	1 x 26 W NE/BK
	599.4068.1.46.00.3	TC-D	G24-d3	1 x 26 W GI/GR
	599.4068.1.46.00.4	TC-D	G24-d3	1 x 26 W AN/AN
	599.4068.1.46.00.0	TC-D	G24-d3	1 x 26 W AR/SI

DL 4068 Graham




Lampada fluorescente compatta elettronica
Electronic compact fluorescent Lamp

	599.4068.1.52.00.1	TC-TEL	GX24-q4	1 x 42 W BI/WH
	599.4068.1.52.00.2	TC-TEL	GX24-q4	1 x 42 W NE/BK
	599.4068.1.52.00.3	TC-TEL	GX24-q4	1 x 42 W GI/GR
	599.4068.1.52.00.4	TC-TEL	GX24-q4	1 x 42 W AN/AN
	599.4068.1.52.00.0	TC-TEL	GX24-q4	1 x 42 W AR/SI

DL 4068 Graham

Lampada incandescenza standard
Standard incandescent Lamp

	599.4068.1.54.00.1	TC-TSE	E27	1 x 23 W BI/WH
	599.4068.1.54.00.2	TC-TSE	E27	1 x 23 W NE/BK
	599.4068.1.54.00.3	TC-TSE	E27	1 x 23 W GI/GR
	599.4068.1.54.00.4	TC-TSE	E27	1 x 23 W AN/AN
	599.4068.1.54.00.0	TC-TSE	E27	1 x 23 W AR/SI

599.9032.A.00.00.Z
Base di ancoraggio
Anchor bolt kit

CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
SELF-EXTINGUISHING IMPACT RESISTANT POLYCARBONATE DIFFUSER WITH UV STABILIZED
ADDITIVE
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

