

**DL 5100 Denise**Lampada alogenuri metallici
Metal halide lamp

	599.5100.1.71.00.1	HIE-CE	E27	1 x 70 W	BI/WH
	599.5100.1.71.00.2	HIE-CE	E27	1 x 70 W	NE/BK
	599.5100.1.71.00.3	HIE-CE	E27	1 x 70 W	GI/GR
	599.5100.1.71.00.4	HIE-CE	E27	1 x 70 W	AN/AN
	599.5100.1.71.00.0	HIE-CE	E27	1 x 70 W	AR/SI

DL 5100 DeniseLampada alogenuri metallici
Metal halide lamp

	599.5100.1.85.00.1	HIT-CE	G12	1 x 35 W	BI/WH
	599.5100.1.85.00.2	HIT-CE	G12	1 x 35 W	NE/BK
	599.5100.1.85.00.3	HIT-CE	G12	1 x 35 W	GI/GR
	599.5100.1.85.00.4	HIT-CE	G12	1 x 35 W	AN/AN
	599.5100.1.85.00.0	HIT-CE	G12	1 x 35 W	AR/SI

DL 5100 DeniseLampada sodio alta pressione
High pressure sodium lamp

	599.5100.1.59.00.1	HSE-I	E27	1 x 70 W	BI/WH
	599.5100.1.59.00.2	HSE-I	E27	1 x 70 W	NE/BK
	599.5100.1.59.00.3	HSE-I	E27	1 x 70 W	GI/GR
	599.5100.1.59.00.4	HSE-I	E27	1 x 70 W	AN/AN
	599.5100.1.59.00.0	HSE-I	E27	1 x 70 W	AR/SI

DL 5100 DeniseLampada fluorescente compatta
Compact fluorescent lamp

	599.5100.1.46.00.1	TC-D	G24-d3	1 x 26 W	BI/WH
	599.5100.1.46.00.2	TC-D	G24-d3	1 x 26 W	NE/BK
	599.5100.1.46.00.3	TC-D	G24-d3	1 x 26 W	GI/GR
	599.5100.1.46.00.4	TC-D	G24-d3	1 x 26 W	AN/AN
	599.5100.1.46.00.0	TC-D	G24-d3	1 x 26 W	AR/SI

DL 5100 DeniseLampada fluorescente compatta
Compact fluorescent lamp



	599.5100.1.52.00.1	TC-TEL	GX24-q4	1 x 42 W	BI/WH
	599.5100.1.52.00.2	TC-TEL	GX24-q4	1 x 42 W	NE/BK
	599.5100.1.52.00.3	TC-TEL	GX24-q4	1 x 42 W	GI/GR
	599.5100.1.52.00.4	TC-TEL	GX24-q4	1 x 42 W	AN/AN
	599.5100.1.52.00.0	TC-TEL	GX24-q4	1 x 42 W	AR/SI

DL 5100 DeniseLampada fluorescente compatta elettronica
Electronic fluorescent lamp


	599.5100.1.54.00.1	TC-TSE	E27	1 x 23 W	BI/WH
	599.5100.1.54.00.2	TC-TSE	E27	1 x 23 W	NE/BK
	599.5100.1.54.00.3	TC-TSE	E27	1 x 23 W	GI/GR
	599.5100.1.54.00.4	TC-TSE	E27	1 x 23 W	AN/AN
	599.5100.1.54.00.0	TC-TSE	E27	1 x 23 W	AR/SI

DL 5100 DeniseLampada alogena
Halogen Lamp

	599.5100.1.24.00.1	QT32	E27	1 x 100 W	BI/WH
	599.5100.1.24.00.2	QT32	E27	1 x 100 W	NE/BK
	599.5100.1.24.00.3	QT32	E27	1 x 100 W	GI/GR
	599.5100.1.24.00.4	QT32	E27	1 x 100 W	AN/AN
	599.5100.1.24.00.0	QT32	E27	1 x 100 W	AR/SI



TC-D G24d-3 26W



TC-TEL GX24q-4 42W

CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

DL 5101 DeniseLampada alogenuri metallici
Metal halide lamp

	599.5101.1.71.00.1	HIE-CE	E27	1 x 70 W	BI/WH
	599.5101.1.71.00.2	HIE-CE	E27	1 x 70 W	NE/BK
	599.5101.1.71.00.3	HIE-CE	E27	1 x 70 W	GI/GR
	599.5101.1.71.00.4	HIE-CE	E27	1 x 70 W	AN/AN
	599.5101.1.71.00.0	HIE-CE	E27	1 x 70 W	AR/SI

DL 5101 DeniseLampada alogenuri metallici
Metal halide lamp

	599.5101.1.85.00.1	HIT-CE	G12	1 x 35 W	BI/WH
	599.5101.1.85.00.2	HIT-CE	G12	1 x 35 W	NE/BK
	599.5101.1.85.00.3	HIT-CE	G12	1 x 35 W	GI/GR
	599.5101.1.85.00.4	HIT-CE	G12	1 x 35 W	AN/AN
	599.5101.1.85.00.0	HIT-CE	G12	1 x 35 W	AR/SI

DL 5101 DeniseLampada sodio alta pressione
High pressure sodium lamp

	599.5101.1.59.00.1	HSE-I	E27	1 x 70 W	BI/WH
	599.5101.1.59.00.2	HSE-I	E27	1 x 70 W	NE/BK
	599.5101.1.59.00.3	HSE-I	E27	1 x 70 W	GI/GR
	599.5101.1.59.00.4	HSE-I	E27	1 x 70 W	AN/AN
	599.5101.1.59.00.0	HSE-I	E27	1 x 70 W	AR/SI

DL 5101 DeniseLampada fluorescente compatta
Compact fluorescent lamp

	599.5101.1.46.00.1	TC-D	G24-d3	1 x 26 W	BI/WH
	599.5101.1.46.00.2	TC-D	G24-d3	1 x 26 W	NE/BK
	599.5101.1.46.00.3	TC-D	G24-d3	1 x 26 W	GI/GR
	599.5101.1.46.00.4	TC-D	G24-d3	1 x 26 W	AN/AN
	599.5101.1.46.00.0	TC-D	G24-d3	1 x 26 W	AR/SI

DL 5101 DeniseLampada fluorescente compatta
Compact fluorescent lamp


	599.5101.1.52.00.1	TC-TEL	GX24-q4	1 x 42 W	BI/WH
	599.5101.1.52.00.2	TC-TEL	GX24-q4	1 x 42 W	NE/BK
	599.5101.1.52.00.3	TC-TEL	GX24-q4	1 x 42 W	GI/GR
	599.5101.1.52.00.4	TC-TEL	GX24-q4	1 x 42 W	AN/AN
	599.5101.1.52.00.0	TC-TEL	GX24-q4	1 x 42 W	AR/SI

DL 5101 DenisetLampada fluorescente compatta elettronica
Electronic fluorescent lamp



	599.5101.1.54.00.1	TC-TSE	E27	1 x 23 W	BI/WH
	599.5101.1.54.00.2	TC-TSE	E27	1 x 23 W	NE/BK
	599.5101.1.54.00.3	TC-TSE	E27	1 x 23 W	GI/GR
	599.5101.1.54.00.4	TC-TSE	E27	1 x 23 W	AN/AN
	599.5101.1.54.00.0	TC-TSE	E27	1 x 23 W	AR/SI

DL 5101 DeniseLampada alogena
Halogen Lamp

	599.5101.1.24.00.1	QT32	E27	1 x 100 W	BI/WH
	599.5101.1.24.00.2	QT32	E27	1 x 100 W	NE/BK
	599.5101.1.24.00.3	QT32	E27	1 x 100 W	GI/GR
	599.5101.1.24.00.4	QT32	E27	1 x 100 W	AN/AN
	599.5101.1.24.00.0	QT32	E27	1 x 100 W	AR/SI



TC-TEL GX24q-4 42W



TC-D G24d-3 26W

CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C