

DL 3500 Martinez

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3500.1.41.00.1	TC	G23	1 x 9 W	BI/WH
	599.3500.1.41.00.2	TC	G23	1 x 9 W	NE/BK
	599.3500.1.41.00.3	TC	G23	1 x 9 W	GI/GR
	599.3500.1.41.00.4	TC	G23	1 x 9 W	AN/AN
	599.3500.1.41.00.0	TC	G23	1 x 9 W	AR/SI

DL 3500 Martinez



Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3500.1.45.00.1	TC-D	G24-d2	1x18 W	BI/WH
	599.3500.1.45.00.2	TC-D	G24-d2	1x18 W	NE/BK
	599.3500.1.45.00.3	TC-D	G24-d2	1x18 W	GI/GR
	599.3500.1.45.00.4	TC-D	G24-d2	1x18 W	AN/AN
	599.3500.1.45.00.0	TC-D	G24-d2	1x18 W	AR/SI


DL 3500 Martinez

Lampada incandescenza
Incandescent Lamp

	599.3500.1.01.00.1	A60	E27	1 x 40 W	BI/WH
	599.3500.1.01.00.2	A60	E27	1 x 40 W	NE/BK
	599.3500.1.01.00.3	A60	E27	1 x 40 W	GI/GR
	599.3500.1.01.00.4	A60	E27	1 x 40 W	AN/AN
	599.3500.1.01.00.0	A60	E27	1 x 40 W	AR/SI



TC-D G24d-2 18W



DL 45 E27 40W



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE
CON PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH
PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 3501 Martinez

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3501.1.41.00.1	TC	G23	1 x 9 W	BI/WH
	599.3501.1.41.00.2	TC	G23	1 x 9 W	NE/BK
	599.3501.1.41.00.3	TC	G23	1 x 9 W	GI/GR
	599.3501.1.41.00.4	TC	G23	1 x 9 W	AN/AN
	599.3501.1.41.00.0	TC	G23	1 x 9 W	AR/SI

DL 3501 Martinez


Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3501.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.3501.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.3501.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.3501.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.3501.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI


DL 3501 Martinez

Lampada incandescenza
Incandescent Lamp


	599.3501.1.01.00.1	A60	E27	1 x 40 W	BI/WH
	599.3501.1.01.00.2	A60	E27	1 x 40 W	NE/BK
	599.3501.1.01.00.3	A60	E27	1 x 40 W	GI/GR
	599.3501.1.01.00.4	A60	E27	1 x 40 W	AN/AN
	599.3501.1.01.00.0	A60	E27	1 x 40 W	AR/SI



TC-D G24d-2 18W



DL 45 E27 40W



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE
CON PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH
PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C







DL 3502 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3502.1.41.00.1	TC	G23	1 x 9 W	BI/WH
	599.3502.1.41.00.2	TC	G23	1 x 9 W	NE/BK
	599.3502.1.41.00.3	TC	G23	1 x 9 W	GI/GR
	599.3502.1.41.00.4	TC	G23	1 x 9 W	AN/AN
	599.3502.1.41.00.0	TC	G23	1 x 9 W	AR/SI

DL 3502 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3502.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.3502.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.3502.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.3502.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.3502.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI

DL 3502 Martinez
Lampada incandescenza
Incandescent Lamp

	599.3502.1.01.00.1	A60	E27	1 x 40 W	BI/WH
	599.3502.1.01.00.2	A60	E27	1 x 40 W	NE/BK
	599.3502.1.01.00.3	A60	E27	1 x 40 W	GI/GR
	599.3502.1.01.00.4	A60	E27	1 x 40 W	AN/AN
	599.3502.1.01.00.0	A60	E27	1 x 40 W	AR/SI

DL 3503 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3503.1.41.00.1	TC	G23	1 x 9 W	BI/WH
	599.3503.1.41.00.2	TC	G23	1 x 9 W	NE/BK
	599.3503.1.41.00.3	TC	G23	1 x 9 W	GI/GR
	599.3503.1.41.00.4	TC	G23	1 x 9 W	AN/AN
	599.3503.1.41.00.0	TC	G23	1 x 9 W	AR/SI

DL 3503 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3503.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.3503.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.3503.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.3503.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.3503.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI

DL 3503 Martinez
Lampada incandescenza
Incandescent Lamp

	599.3503.1.01.00.1	A60	E27	1 x 40 W	BI/WH
	599.3503.1.01.00.2	A60	E27	1 x 40 W	NE/BK
	599.3503.1.01.00.3	A60	E27	1 x 40 W	GI/GR
	599.3503.1.01.00.4	A60	E27	1 x 40 W	AN/AN
	599.3503.1.01.00.0	A60	E27	1 x 40 W	AR/SI



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 3504 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3504.1.41.00.1	TC	G23	1 x 9 W	BI/WH
	599.3504.1.41.00.2	TC	G23	1 x 9 W	NE/BK
	599.3504.1.41.00.3	TC	G23	1 x 9 W	GI/GR
	599.3504.1.41.00.4	TC	G23	1 x 9 W	AN/AN
	599.3504.1.41.00.0	TC	G23	1 x 9 W	AR/SI

DL 3504 Martinez
Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3504.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.3504.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.3504.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.3504.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.3504.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI

DL 3504 Martinez
Lampada incandescenza
Incandescent Lamp

	599.3504.1.01.00.1	A60	E27	1 x 40 W	BI/WH
	599.3504.1.01.00.2	A60	E27	1 x 40 W	NE/BK
	599.3504.1.01.00.3	A60	E27	1 x 40 W	GI/GR
	599.3504.1.01.00.4	A60	E27	1 x 40 W	AN/AN
	599.3504.1.01.00.0	A60	E27	1 x 40 W	AR/SI



TC-D G24d-2 18W



D45 E27 40W



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 3510 Martinez

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3510.1.42.00.1	TC	G23	1 x 11 W BI/WH
	599.3510.1.42.00.2	TC	G23	1 x 11 W NE/BK
	599.3510.1.42.00.3	TC	G23	1 x 11 W GI/GR
	599.3510.1.42.00.4	TC	G23	1 x 11 W AN/AN
	599.3510.1.42.00.0	TC	G23	1 x 11 W AR/SI

DL 3510 Martinez


Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3510.1.46.00.1	TC-D	G24-d3	1 x 26 W BI/WH
	599.3510.1.46.00.2	TC-D	G24-d3	1 x 26 W NE/BK
	599.3510.1.46.00.3	TC-D	G24-d3	1 x 26 W GI/GR
	599.3510.1.46.00.4	TC-D	G24-d3	1 x 26 W AN/AN
	599.3510.1.46.00.0	TC-D	G24-d3	1 x 26 W AR/SI

DL 3510 Martinez

Lampada incandescenza
Incandescent Lamp

	599.3510.1.02.00.1	A60	E27	1 x 60 W BI/WH
	599.3510.1.02.00.2	A60	E27	1 x 60 W NE/BK
	599.3510.1.02.00.3	A60	E27	1 x 60 W GI/GR
	599.3510.1.02.00.4	A60	E27	1 x 60 W AN/AN
	599.3510.1.02.00.0	A60	E27	1 x 60 W AR/SI



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON
PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH
PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

DL 3511 Martinez

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3511.1.42.00.1	TC	G23	1 x 11 W BI/WH
	599.3511.1.42.00.2	TC	G23	1 x 11 W NE/BK
	599.3511.1.42.00.3	TC	G23	1 x 11 W GI/GR
	599.3511.1.42.00.4	TC	G23	1 x 11 W AN/AN
	599.3511.1.42.00.0	TC	G23	1 x 11 W AR/SI

DL 3511 Martinez


Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3511.1.46.00.1	TC-D	G24-d3	1 x 26 W BI/WH
	599.3511.1.46.00.2	TC-D	G24-d3	1 x 26 W NE/BK
	599.3511.1.46.00.3	TC-D	G24-d3	1 x 26 W GI/GR
	599.3511.1.46.00.4	TC-D	G24-d3	1 x 26 W AN/AN
	599.3511.1.46.00.0	TC-D	G24-d3	1 x 26 W AR/SI

DL 3511 Martinez

Lampada incandescenza
Incandescent Lamp

	599.3511.1.02.00.1	A60	E27	1 x 60 W BI/WH
	599.3511.1.02.00.2	A60	E27	1 x 60 W NE/BK
	599.3511.1.02.00.3	A60	E27	1 x 60 W GI/GR
	599.3511.1.02.00.4	A60	E27	1 x 60 W AN/AN
	599.3511.1.02.00.0	A60	E27	1 x 60 W AR/SI



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON
PRETRATTAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH
PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C