


**DL 3815 Omega**Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3815.1.46.00.1	TC-D	G24-d3	1 x 26 W	BI/WH
	599.3815.1.46.00.2	TC-D	G24-d3	1 x 26 W	NE/BK
	599.3815.1.46.00.3	TC-D	G24-d3	1 x 26 W	GI/GR
	599.3815.1.46.00.4	TC-D	G24-d3	1 x 26 W	AN/AN
	599.3815.1.46.00.0	TC-D	G24-d3	1 x 26 W	AR/SI

DL 3815 OmegaLampada incandescenza standard
Standard incandescent Lamp

	599.3815.2.46.00.1	TC-D	G24-d3	2 x 26 W	BI/WH
	599.3815.2.46.00.2	TC-D	G24-d3	2 x 26 W	NE/BK
	599.3815.2.46.00.3	TC-D	G24-d3	2 x 26 W	GI/GR
	599.3815.2.46.00.4	TC-D	G24-d3	2 x 26 W	AN/AN
	599.3815.2.46.00.0	TC-D	G24-d3	2 x 26 W	AR/SI

DL 3815 OmegaLampada alogena
Halogen Lamp

	599.3815.1.23.00.1	QT32	E27	1 x 60 W	BI/WH
	599.3815.1.23.00.2	QT32	E27	1 x 60 W	NE/BK
	599.3815.1.23.00.3	QT32	E27	1 x 60 W	GI/GR
	599.3815.1.23.00.4	QT32	E27	1 x 60 W	AN/AN
	599.3815.1.23.00.0	QT32	E27	1 x 60 W	AR/SI



Scatola per installazione da incasso inclusa

Wall installation housing included



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRAT-
TAMENTO SPECIALE PER ESTERNI
CASSAFORMA IN PA 6.6
VETRO DI PROTEZIONE TEMPERATO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH
PRETREATMENT FOR OUTDOOR USE
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SAFETY TEMPERED GLASS
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C