




DL 5202 Tunder
Lampada alogena bassa tensione con riflettore incorporato
Low voltage reflector lamp

	599.5202.1.11.00.5	QR-CB51	G5,3	1 x 50 W INOX
---	--------------------	---------	------	---------------


DL 5202 Tunder
Lampada alogena con riflettore incorporato 230 V
Reflector halogen lamp 230 V

	599.5202.1.04.00.5	QPAR16	GU10	1 x 50 W INOX
---	--------------------	--------	------	---------------

DL 5202 Tunder
Sorgente LED
LED emitter


	599.5202.1.L2.00.5	LED-WHITE CABLE	3 x 1 W	INOX
---	--------------------	-----------------	---------	------

DL 5202 Tunder
Sorgente LED
LED emitter


	599.5202.1.L3.00.5	LED-RGB CABLE	3 x 1 W	INOX
---	--------------------	---------------	---------	------

A RICHIESTA : SISTEMA DI CONTROLLO RGB - CENTRALINA - TELECOMANDO

DL 5202 Tunder
Lampada fluorescente compatta elettronica
Electronic fluorescent lamp

	599.5202.1.96.00.5	TC-TSE	GX53	1 x 7 W	INOX
---	--------------------	--------	------	---------	------

DL 5203 Tunder
Lampada alogena bassa tensione con riflettore incorporato
Low voltage reflector lamp

	599.5203.1.11.00.5	QR-CB51	G5,3	1 x 50 W	INOX
---	--------------------	---------	------	----------	------

DL 5203 Tunder
Lampada alogena con riflettore incorporato 230 V
Reflector halogen lamp 230 V

	599.5203.1.04.00.5	QPAR16	GU10	1 x 50 W	INOX
---	--------------------	--------	------	----------	------

DL 5203 Tunder
Sorgente LED
LED emitter

	599.5203.1.L2.00.5	LED-WHITE CABLE	3 x 1 W	INOX
---	--------------------	-----------------	---------	------

DL 5203 Tunder
Sorgente LED
LED emitter

	599.5203.1.L3.00.5	LED-RGB CABLE	3 x 1 W	INOX
---	--------------------	---------------	---------	------


A RICHIESTA : SISTEMA DI CONTROLLO RGB - CENTRALINA - TELECOMANDO

DL 5203 Tunder
Lampada fluorescente compatta elettronica
Electronic fluorescent lamp


	599.5203.1.96.00.5	TC-TSE	GX53	1 x 7 W	INOX
---	--------------------	--------	------	---------	------



VETRO TRASPARENTE
CLEAR GLASS




130




105

Scatola per installazione da incasso inclusa
Wall installation housing included




QR-CB51 GU5.3 50W



QR-CB51 GU5.3 50W



VETRO SABBBIATO
FROSTED GLASS



130



105

Scatola per installazione da incasso inclusa
Wall installation housing included



CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
ANELLO DI CHIUSURA IN ACCIAIO INOX SATINATO
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
FRONT COVER IN ANTI-CORROSION STAINLESS STEEL IN SATIN FINISHING
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

CORPO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
ANELLO DI CHIUSURA IN ACCIAIO INOX SATINATO
CASSAFORMA IN PA 6.6
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
FRONT COVER IN ANTI-CORROSION STAINLESS STEEL IN SATIN FINISHING
WALL INSTALLATION HOUSING IN POLYAMID PA 6.6
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREW
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C