



DL 3104 Penny

Lampada alogena con riflettore incorporato
Reflector halogen lamp

	599.3104.1.05.00.1	PAR20	E27	1 x 50 W	BI/WH
	599.3104.1.05.00.2	PAR20	E27	1 x 50 W	NE/BK
	599.3104.1.05.00.3	PAR20	E27	1 x 50 W	GI/GR
	599.3104.1.05.00.4	PAR20	E27	1 x 50 W	AN/AN
	599.3104.1.05.00.0	PAR20	E27	1 x 50 W	AR/SI


DL 3104 Penny

Lampada alogena con riflettore incorporato 230 V
Reflector halogen lamp 230 V

	599.3104.1.04.00.1	QPAR16	GU10	1 x 50 W	BI/WH
	599.3104.1.04.00.2	QPAR16	GU10	1 x 50 W	NE/BK
	599.3104.1.04.00.3	QPAR16	GU10	1 x 50 W	GI/GR
	599.3104.1.04.00.4	QPAR16	GU10	1 x 50 W	AN/AN
	599.3104.1.04.00.0	QPAR16	GU10	1 x 50 W	AR/SI


DL 3104 Penny

Lampada fluorescente 230 V con riflettore incorporato
Reflector florescent lamp 230 V

	599.3104.1.96.00.1	TC-TSE	GU10	1 x 7 W	BI/WH
	599.3104.1.96.00.2	TC-TSE	GU10	1 x 7 W	NE/BK
	599.3104.1.96.00.3	TC-TSE	GU10	1 x 7 W	GI/GR
	599.3104.1.96.00.4	TC-TSE	GU10	1 x 7 W	AN/AN
	599.3104.1.96.00.0	TC-TSE	GU10	1 x 7 W	AR/SI


DL 3105 Penny

Lampada alogena con riflettore incorporato
Reflector halogen lamp

	599.3105.1.06.00.1	PAR30	E27	1 x 75 W	BI/WH
	599.3105.1.06.00.2	PAR30	E27	1 x 75 W	NE/BK
	599.3105.1.06.00.3	PAR30	E27	1 x 75 W	GI/GR
	599.3105.1.06.00.4	PAR30	E27	1 x 75 W	AN/AN
	599.3105.1.06.00.0	PAR30	E27	1 x 75 W	AR/SI

DL 3106 Penny

Lampada alogena con riflettore incorporato
Reflector halogen lamp


	599.3106.1.08.00.1	PAR38	E27	1 x 100 W	BI/WH
	599.3106.1.08.00.2	PAR38	E27	1 x 100 W	NE/BK
	599.3106.1.08.00.3	PAR38	E27	1 x 100 W	GI/GR
	599.3106.1.08.00.4	PAR38	E27	1 x 100 W	AN/AN
	599.3106.1.08.00.0	PAR38	E27	1 x 100 W	AR/SI



DL 3104 : A = 160 B = 165 C = 105

DL 3105 : A = 195 B = 220 C = 140

DL 3106 : A = 215 B = 255 C = 175



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C