



DL 3110 Ariell

Lampada fluorescente compatta
Compact fluorescent lamp

	599.3110.2.46.00.1	TC-D	G24-d3 2 x 26 W	BI/WH
	599.3110.2.46.00.2	TC-D	G24-d3 2 x 26 W	NE/BK
	599.3110.2.46.00.3	TC-D	G24-d3 2 x 26 W	GI/GR
	599.3110.2.46.00.4	TC-D	G24-d3 2 x 26 W	AN/AN
	599.3110.2.46.00.0	TC-D	G24-d3 2 x 26 W	AR/SI

DL 3110 Ariell


Lampada fluorescente compatta
Compact fluorescent lamp

	599.3110.2.52.00.1	TC-TEL	GX24-q4 2 x 42 W	BI/WH
	599.3110.2.52.00.2	TC-TEL	GX24-q4 2 x 42 W	NE/BK
	599.3110.2.52.00.3	TC-TEL	GX24-q4 2 x 42 W	GI/GR
	599.3110.2.52.00.4	TC-TEL	GX24-q4 2 x 42 W	AN/AN
	599.3110.2.52.00.0	TC-TEL	GX24-q4 2 x 42 W	AR/SI


DL 3110 Ariell

Lampada alogenuri metallici STANDARD FASCIO MEDIO
Metal halide lamp STANDARD MEDIUM BEAM


	599.3110.2.86.00.1	HIT-CE	G12 2 x 70 W	BI/WH
	599.3110.2.86.00.2	HIT-CE	G12 2 x 70 W	NE/BK
	599.3110.2.86.00.3	HIT-CE	G12 2 x 70 W	GI/GR
	599.3110.2.86.00.4	HIT-CE	G12 2 x 70 W	AN/AN
	599.3110.2.86.00.0	HIT-CE	G12 2 x 70 W	AR/SI




HIT-CE G12 2x70 W
STANDARD MEDIUM BEAM




HIT-CE G12 2x70 W
WIDE BEAM




TC-D G24d-3 2x26 W



TC-TEL GX24q-4 2x42 W



HIT-CE G12 2x70 W
NARROW BEAM



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 3111 Ariell

Lampada con riflettore incorporato
Reflector Lamp

	599.3111.1.46.00.1	TC-D	G24-d3 1 x 26 W	BI/WH
	599.3111.1.46.00.2	TC-D	G24-d3 1 x 26 W	NE/BK
	599.3111.1.46.00.3	TC-D	G24-d3 1 x 26 W	GI/GR
	599.3111.1.46.00.4	TC-D	G24-d3 1 x 26 W	AN/AN
	599.3111.1.46.00.0	TC-D	G24-d3 1 x 26 W	AR/SI

DL 3111 Ariell


Lampada fluorescente compatta
Compact fluorescent lamp

	599.3111.1.52.00.1	TC-TEL	GX24-q4 1 x 42 W	BI/WH
	599.3111.1.52.00.2	TC-TEL	GX24-q4 1 x 42 W	NE/BK
	599.3111.1.52.00.3	TC-TEL	GX24-q4 1 x 42 W	GI/GR
	599.3111.1.52.00.4	TC-TEL	GX24-q4 1 x 42 W	AN/AN
	599.3111.1.52.00.0	TC-TEL	GX24-q4 1 x 42 W	AR/SI


DL 3111 Ariell

Lampada alogenuri metallici STANDARD FASCIO MEDIO
Metal halide lamp STANDARD MEDIUM BEAM


	599.3111.1.86.00.1	HIT-CE	G12 1 x 70 W	BI/WH
	599.3111.1.86.00.2	HIT-CE	G12 1 x 70 W	NE/BK
	599.3111.1.86.00.3	HIT-CE	G12 1 x 70 W	GI/GR
	599.3111.1.86.00.4	HIT-CE	G12 1 x 70 W	AN/AN
	599.3111.1.86.00.0	HIT-CE	G12 1 x 70 W	AR/SI




HIT-CE G12 2x70 W
STANDARD MEDIUM BEAM




HIT-CE G12 2x70 W
WIDE BEAM




TC-D G24d-3 26W



TC-TEL GX24q-4 42W



HIT-CE G12 2x70 W
NARROW BEAM



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

DL 3112 AriellLampada alogenuri metallici
Metal halide lamp


599.3112.1.85.00.1	HIT-CE	G12	1 x 35 W	BI/WH
599.3112.1.85.00.2	HIT-CE	G12	1 x 35 W	NE/BK
599.3112.1.85.00.3	HIT-CE	G12	1 x 35 W	GI/GR
599.3112.1.85.00.4	HIT-CE	G12	1 x 35 W	AN/AN
599.3112.1.85.00.0	HIT-CE	G12	1 x 35 W	AR/SI

DL 3112 AriellLampada alogenuri metallici
Metal halide lamp

599.3112.1.86.00.1	HIT-CE	G12	1 x 70 W	BI/WH
599.3112.1.86.00.2	HIT-CE	G12	1 x 70 W	NE/BK
599.3112.1.86.00.3	HIT-CE	G12	1 x 70 W	GI/GR
599.3112.1.86.00.4	HIT-CE	G12	1 x 70 W	AN/AN
599.3112.1.86.00.0	HIT-CE	G12	1 x 70 W	AR/SI



NEW



CORPO IN ALLUMINIO ESTRUSO S6063
 COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
 POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
 VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
 VITERIA IN ACCIAIO INOX
 GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
 COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
 POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
 SAFETY TEMPERED GLASS
 HIGH PURITY ALUMINIUM REFLECTOR
 STAINLESS STEEL SCREWS
 WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

