




3980



TC G23 2x9W DL3980



3981



TC-D G24d-3 2x26W DL3981



## DL 3980 Gila

Lampada fluorescente compatta  
Compact fluorescent Lamp

	599.3980.2.41.00.1	TC	G23	2 x 9 W	BI/WH
	599.3980.2.41.00.2	TC	G23	2 x 9 W	NE/BK
	599.3980.2.41.00.3	TC	G23	2 x 9 W	GI/GR
	599.3980.2.41.00.4	TC	G23	2 x 9 W	AN/AN
	599.3980.2.41.00.0	TC	G23	2 x 9 W	AR/SI

## DL 3980 Gila

Lampada fluorescente compatta  
Compact fluorescent Lamp

	599.3980.2.45.00.1	TC-D	G24-d2	2 x 18 W	BI/WH
	599.3980.2.45.00.2	TC-D	G24-d2	2 x 18 W	NE/BK
	599.3980.2.45.00.3	TC-D	G24-d2	2 x 18 W	GI/GR
	599.3980.2.45.00.4	TC-D	G24-d2	2 x 18 W	AN/AN
	599.3980.2.45.00.0	TC-D	G24-d2	2 x 18 W	AR/SI

## DL 3980 Gila

Lampada fluorescente compatta  
Compact fluorescent Lamp

	599.3980.1.46.00.1	TC-D	G24-d3	1 x 26 W	BI/WH
	599.3980.1.46.00.2	TC-D	G24-d3	1 x 26 W	NE/BK
	599.3980.1.46.00.3	TC-D	G24-d3	1 x 26 W	GI/GR
	599.3980.1.46.00.4	TC-D	G24-d3	1 x 26 W	AN/AN
	599.3980.1.46.00.0	TC-D	G24-d3	1 x 26 W	AR/SI

## DL 3981 Gila

Lampada fluorescente compatta  
Compact fluorescent Lamp

	599.3981.2.46.00.1	TC-D	G24-d3	2 x 26 W	BI/WH
	599.3981.2.46.00.2	TC-D	G24-d3	2 x 26 W	NE/BK
	599.3981.2.46.00.3	TC-D	G24-d3	2 x 26 W	GI/GR
	599.3981.2.46.00.4	TC-D	G24-d3	2 x 26 W	AN/AN
	599.3981.2.46.00.0	TC-D	G24-d3	2 x 26 W	AR/SI

## DL 3981 Gila

Lampada fluorescente compatta  
Compact fluorescent Lamp

	599.3981.2.52.00.1	TC-TEL	GX24-q4	2 x 42 W	BI/WH
	599.3981.2.52.00.2	TC-TEL	GX24-q4	2 x 42 W	NE/BK
	599.3981.2.52.00.3	TC-TEL	GX24-q4	2 x 42 W	GI/GR
	599.3981.2.52.00.4	TC-TEL	GX24-q4	2 x 42 W	AN/AN
	599.3981.2.52.00.0	TC-TEL	GX24-q4	2 x 42 W	AR/SI

## DL 3981 Gila

Lampada fluorescente compatta elettronica  
Electronic fluorescent lamp

	599.3981.2.54.00.1	TC-TSE	E27	2 x 23 W	BI/WH
	599.3981.2.54.00.2	TC-TSE	E27	2 x 23 W	NE/BK
	599.3981.2.54.00.3	TC-TSE	E27	2 x 23 W	GI/GR
	599.3981.2.54.00.4	TC-TSE	E27	2 x 23 W	AN/AN
	599.3981.2.54.00.0	TC-TSE	E27	2 x 23 W	AR/SI

## DL 3981 Gila

Lampada fluorescente compatta elettronica  
Electronic fluorescent lamp

	599.3981.1.24.00.1	QT32	E27	1x100 W	BI/WH
	599.3981.1.24.00.2	QT32	E27	1x100 W	NE/BK
	599.3981.1.24.00.3	QT32	E27	1x100 W	GI/GR
	599.3981.1.24.00.4	QT32	E27	1x100 W	AN/AN
	599.3981.1.24.00.0	QT32	E27	1x100 W	AR/SI

CORPO E ANELLO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI  
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV  
VITERIA IN ACCIAIO INOX  
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY AND FRONT COVER IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE  
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE STAINLESS STEEL SCREWS  
WEATHER PROOF AND DURABLE SILICONE GASKET.  
SERVICE TEMPERATURE -40° +250°C