


DL 4175 Hardlight

Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4175.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.4175.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.4175.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.4175.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.4175.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI


DL 4175 Hardlight


Lampada fluorescente compatta
Compact fluorescent Lamp

	599.4175.1.53.00.1	TC-TSE	E27	1 x 15 W	BI/WH
	599.4175.1.53.00.2	TC-TSE	E27	1 x 15 W	NE/BK
	599.4175.1.53.00.3	TC-TSE	E27	1 x 15 W	GI/GR
	599.4175.1.53.00.4	TC-TSE	E27	1 x 15 W	AN/AN
	599.4175.1.53.00.0	TC-TSE	E27	1 x 15 W	AR/SI


DL 4175 Hardlight

Lampada fluorescente compatta elettronica
Electronic compact fluorescent Lamp

	599.4175.1.23.00.1	QT32	E27	1 x 60 W	BI/WH
	599.4175.1.23.00.2	QT32	E27	1 x 60 W	NE/BK
	599.4175.1.23.00.3	QT32	E27	1 x 60 W	GI/GR
	599.4175.1.23.00.4	QT32	E27	1 x 60 W	AN/AN
	599.4175.1.23.00.0	QT32	E27	1 x 60 W	AR/SI



TC-D G24d-2 18W



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
SELF-EXTINGUISHING IMPACT RESISTANT POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
RIFLETTORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C