

DL 3140 Rubens

Lampada alogena
Halogen Lamp

/	599.3140.2.17.00.1	QT-DE12	R7s	2 x 150 W	BI/WH
/	599.3140.2.17.00.2	QT-DE12	R7s	2 x 150 W	NE/BK
/	599.3140.2.17.00.3	QT-DE12	R7s	2 x 150 W	GI/GR
/	599.3140.2.17.00.4	QT-DE12	R7s	2 x 150 W	AN/AN
/	599.3140.2.17.00.0	QT-DE12	R7s	2 x 150 W	AR/SI



DL 3140 Rubens

Lampada alogenuri metallici
Metal halide lamp

/	599.3140.2.85.00.1	HIT-CE	G12	2 x 35 W	BI/WH
/	599.3140.2.85.00.2	HIT-CE	G12	2 x 35 W	NE/BK
/	599.3140.2.85.00.3	HIT-CE	G12	2 x 35 W	GI/GR
/	599.3140.2.85.00.4	HIT-CE	G12	2 x 35 W	AN/AN
/	599.3140.2.85.00.0	HIT-CE	G12	2 x 35 W	AR/SI



NEW



TC-D G24d-3 26W



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C



DL 3141 Rubens

Lampada alogena
Halogen Lamp

/	599.3141.1.17.00.1	QT-DE12	R7s	1 x 150 W	BI/WH
/	599.3141.1.17.00.2	QT-DE12	R7s	1 x 150 W	NE/BK
/	599.3141.1.17.00.3	QT-DE12	R7s	1 x 150 W	GI/GR
/	599.3141.1.17.00.4	QT-DE12	R7s	1 x 150 W	AN/AN
/	599.3141.1.17.00.0	QT-DE12	R7s	1 x 150 W	AR/SI

DL 3141 Rubens

Lampada alogenuri metallici
Metal halide lamp

/	599.3141.1.86.00.1	HIT-CE	G12	1 x 70 W	BI/WH
/	599.3141.1.86.00.2	HIT-CE	G12	1 x 70 W	NE/BK
/	599.3141.1.86.00.3	HIT-CE	G12	1 x 70 W	GI/GR
/	599.3141.1.86.00.4	HIT-CE	G12	1 x 70 W	AN/AN
/	599.3141.1.86.00.0	HIT-CE	G12	1 x 70 W	AR/SI


DL 3141 Rubens

Lampada alogenuri metallici
Metal halide lamp


/	599.3141.1.79.00.1	HIT-DE-CE	Rx7s	1 x 70 W	BI/WH
/	599.3141.1.79.00.2	HIT-DE-CE	Rx7s	1 x 70 W	NE/BK
/	599.3141.1.79.00.3	HIT-DE-CE	Rx7s	1 x 70 W	GI/GR
/	599.3141.1.79.00.4	HIT-DE-CE	Rx7s	1 x 70 W	AN/AN
/	599.3141.1.79.00.0	HIT-DE-CE	Rx7s	1 x 70 W	AR/SI



NEW



TC-D G24d-3 26W



CORPO IN ALLUMINIO ESTRUSO S6063
COPERCHI E BASE DI FISSAGGIO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A
POLVERE CON PRETRATTAMENTO SPECIALE PER ESTERNI
VETRO DI PROTEZIONE TEMPERATORIFLETORE IN ALLUMINIO PURISSIMO
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY IN CORROSION RESISTANT EXTRUSION ALUMINIUM S6063
COVERS AND WALL BRACKET IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY
POWDER COATED WITH PRETREATMENT FOR OUTDOOR USE
SAFETY TEMPERED GLASS
HIGH PURITY ALUMINIUM REFLECTOR
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

