



DL 3911 Kawa



Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3911.2.41.00.1	TC	G23	2 x 9 W	BI/WH
	599.3911.2.41.00.2	TC	G23	2 x 9 W	NE/BK
	599.3911.2.41.00.3	TC	G23	2 x 9 W	GI/GR
	599.3911.2.41.00.4	TC	G23	2 x 9 W	AN/AN
	599.3911.2.41.00.0	TC	G23	2 x 9 W	AR/SI


DL 3911 Kawa

Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3911.1.45.00.1	TC-D	G24-d2	1 x 18 W	BI/WH
	599.3911.1.45.00.2	TC-D	G24-d2	1 x 18 W	NE/BK
	599.3911.1.45.00.3	TC-D	G24-d2	1 x 18 W	GI/GR
	599.3911.1.45.00.4	TC-D	G24-d2	1 x 18 W	AN/AN
	599.3911.1.45.00.0	TC-D	G24-d2	1 x 18 W	AR/SI



TC G23 2x9W



TC-D G24d-2 18W



A60 E27 60W



CORPO E ANELLO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON
PRETRATTAMENTO SPECIALE PER ESTERNI
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY AND FRONT COVER IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER
COATED WITH PRETREATMENT FOR OUTDOOR USE
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

DL 3912 Kawa

Lampada ad alogenuri metallici
Metal halide Lamp

	599.3912.1.71.00.1	HIE-CE	E27	1 x 70 W	BI/WH
	599.3912.1.71.00.2	HIE-CE	E27	1 x 70 W	NE/BK
	599.3912.1.71.00.3	HIE-CE	E27	1 x 70 W	GI/GR
	599.3912.1.71.00.4	HIE-CE	E27	1 x 70 W	AN/AN
	599.3912.1.71.00.0	HIE-CE	E27	1 x 70 W	AR/SI

DL 3912 Kawa

Lampada al sodio alta pressione
High pressure sodium lamp

	599.3912.1.59.00.1	HSE-I	E27	1 x 70 W	BI/WH
	599.3912.1.59.00.2	HSE-I	E27	1 x 70 W	NE/BK
	599.3912.1.59.00.3	HSE-I	E27	1 x 70 W	GI/GR
	599.3912.1.59.00.4	HSE-I	E27	1 x 70 W	AN/AN
	599.3912.1.59.00.0	HSE-I	E27	1 x 70 W	AR/SI

DL 3912 Kawa

Lampada a vapori di mercurio
Mercury vapor Lamp

	599.3912.1.55.00.1	HME	E27	1 x 80 W	BI/WH
	599.3912.1.55.00.2	HME	E27	1 x 80 W	NE/BK
	599.3912.1.55.00.3	HME	E27	1 x 80 W	GI/GR
	599.3912.1.55.00.4	HME	E27	1 x 80 W	AN/AN
	599.3912.1.55.00.0	HME	E27	1 x 80 W	AR/SI

DL 3912 Kawa


Lampada fluorescente compatta
Compact fluorescent Lamp

	599.3912.2.46.00.1	TC-D	G24-d3	2 x 26 W	BI/WH
	599.3912.2.46.00.2	TC-D	G24-d3	2 x 26 W	NE/BK
	599.3912.2.46.00.3	TC-D	G24-d3	2 x 26 W	GI/GR
	599.3912.2.46.00.4	TC-D	G24-d3	2 x 26 W	AN/AN
	599.3912.2.46.00.0	TC-D	G24-d3	2 x 26 W	AR/SI


DL 3912 Kawa

Lampada fluorescente compatta
Compact fluorescent Lamp


	599.3912.2.52.00.1	TC-TEL	GX24-q4	2 x 42 W	BI/WH
	599.3912.2.52.00.2	TC-TEL	GX24-q4	2 x 42 W	NE/BK
	599.3912.2.52.00.3	TC-TEL	GX24-q4	2 x 42 W	GI/GR
	599.3912.2.52.00.4	TC-TEL	GX24-q4	2 x 42 W	AN/AN
	599.3912.2.52.00.0	TC-TEL	GX24-q4	2 x 42 W	AR/SI




HIE-CE E27 70W



TC-D G24d-3 2x26W



TC-TEL GX24Q-4 2x42W



CORPO E ANELLO IN PRESSOFUSIONE DI ALLUMINIO ADC12 VERNICIATO A POLVERE CON
PRETRATTAMENTO SPECIALE PER ESTERNI
DIFFUSORE IN POLICARBONATO AUTOESTINGUENTE STABILIZZATO UV
VITERIA IN ACCIAIO INOX
GUARNIZIONI IN GOMMA SILICONICA. TEMPERATURA DI SERVIZIO -40° +250°C

BODY AND FRONT COVER IN HIGH-PRESSURE DIE-CAST ALUMINIUM ADC12 ALLOY POWDER
COATED WITH PRETREATMENT FOR OUTDOOR USE
SELF-EXTINGUISHING POLYCARBONATE DIFFUSER WITH UV STABILIZED ADDITIVE
STAINLESS STEEL SCREWS
WEATHER PROOF AND DURABLE SILICONE GASKET. SERVICE TEMPERATURE -40° +250°C

