



"5000"



Residential, Urban Lighting

"5000" outdoor light fitting that thanks to its technical peculiarities is easily adaptable in different environments.

Wall - ceiling or pole fixture for compact fluorescent lamps 9, 11 or 18W.

Emergency/continuous light available IP54.

"5000"

A5002GR




Code	Lamps Watt	
A5002 BI•GR•NE	1x11	FSD G23
A5004 BI•GR•NE	1x18	FSD 2G11

Code	Lamps Watt		emergency
A5002/SE BI•GR•NE	1x11	FSD 2G7	



Colours
NE 



Code

A5000
Fiberglass pole



Indoor or outdoor light fittings IP54.

Base in white, black or grey thermoplastic material provided with sealing rubber and duct for cable passage \varnothing 8 mm. Reflector in white zinc coated steel. Wiring tray.

Diffuser transparent and glazed metacrylate fixed on the base by inoxidizable screws.


Starter Wiring 230V-50Hz for fluorescent lamps, electrical components with ENEC approval. Rigid cable H05V2-U section 0,75 mm² (CEI 20-20). Socket

terminal 2P+T (section max 2,5 mm²). Installations ceiling, wall or rectangular pole A5000.

Accessories provided screws and fastening nogs.

In accordance with standard IEC 598, CEI EN 60598-1 (CEI 34-21).

Emergency wiring in accordance with standard CEI EN 60598-2-22 (CEI 34-22).



Colours

BI 
GR 
NE 