



Pico



Residential, Urban Lighting

Adjustable small projector for applications to ground with peg, to floor or for wall.

Ideal for illumination of accent for outside and inside floral fitting out, and for private residential gardens.

PICO mounts the white Golden Dragon® LED, able to guarantee a high luminous efficiency.

High protection rating IP67: completely dust-proof and against temporary immersion.



Pico

E140D1003GB



Code	Lamps Watt
------	---------------

S140D1006GB	3,6-6
S140D1006NB	3,6-6

Light fitting without transformer.

Code	Output	LED Watt	n° light fittings
------	--------	-------------	-------------------

E140K2006KK	500mA 12W	6	max 2
E140K4003KK	350mA 15W	3,6	max 4

Electronic transformer 220-240V 50/60 Hz, IP20, class II.

Code	LED Watt
------	-------------

E140D1003GB	3,6
E140D1003NB	3,6

Light fitting with electronic transformer 3,6W - 350 mA and supply cable H05RN-F 2x1 mm² L=2000 mm. Sealed version: maintenance not allowed.




Adjustable small projector for applications to ground, to floor or for wall.

Body in high resistant thermoplastic. Safety screen in clear polycarbonate, shockproof and unalterable, with a high UV stability reating.

Circuit board of 3 white LED

Golden Dragon® 3,6 / 6 Watt, supplied by a constant extra low voltage current 350/500mA. Aluminium heat dissipator. EDPM seal and stainless steel screws. Double cable gland PG7 (for cables 4 to 7 mm²). Recommended supply cable

H05RN-F 2x1 mm² (L max 30 mt.) Ground-peg in high resistant thermoplastic.



Colours



