

Dinamis is a wall-mounted projector with a distinctive, compact design. Its class II high quality and strong materials and IP 65 protection allow to use this luminaire for indoor and outdoor lighting. The projector was designed with a focus on details: installation is easier thanks to the isolator situated on the wall mounting plate which is connected to the mains power supply. This solution allows to fix the plate alone, with following slip-on connection (through the isolator) when the lamp housing is secured.


Technical specifications

The projector housing is entirely made of die-cast aluminium and is complete with an upper louver in tempered glass. Silicone gaskets and stainless steel screws make it solid and weather-proof. The luminaire with UV-stabilized epoxy polyester coat finish is offered in three colours: white, grey, anthracite grey.

Structural features

Installation: wall
Luminaire housing: die-cast aluminium
Louvers: tempered glass
Light sources: 1W LED
Standard finishing: white, grey, anthracite
Protection class: IP65
Insulation class: II
Power supply: 230V - 50Hz

DESIGN - STEFANO DALL'OSSO

Adjustable wall-mounted luminaire with direct and indirect light for LED light sources.
Equipped with ballast and receiver.
Front protection louver in tempered glass.
Insulation class: II 


CODE	DESCRIPTION
2800/RGB	7.1W LEDs per colour 190/265V AC - 50/60Hz 45° beam opening Colour: 01 - 18 - 19 IP 65 Weight 5.8 Kg



ACCESSORIES

450	Remote control It allows to switch on and off and to adjust the light intensity of the colour flow
-----	--

Size (mm)



NOTE

- 01 white
- 18 grey
- 19 anthracite