



HIGH  
LIGHTS  
2010

# SATURN LED



- AREAS WITH REDUCED TRAFFIC
- ACCESS AND MINOR ROADS
- PEDESTRIAN PRECINCTS
- PUBLIC PARKS



**SATURN LED**  
luminaire for Ø 90mm pole top, designed for mounting on recommended poles.

Luminaire housing made of die-cast aluminium, aluminium, stainless steel, stainless steel threaded inserts, clear PC cylinder, polished stainless steel canopy with integral secondary reflector, four High Efficiency LED modules, thermal management controlled by a two-part heat sink made of die-cast aluminium with a copper core, Ø: 720mm, H: 626mm, protective rating IP65, safety category I, safety category II optional, standard colour: graphite-mica finish [-4] or colour on request [-9].

Windage area: 0.170m<sup>2</sup>, weight: 19.6kg

**Pole top luminaire SX 470** - -  
without pole

**LED**

		60W → <b>7 0</b>		
	High Comfort 4000K MTR-LED symmetrical	LVK → 8217		
		60W → <b>6 0</b>		
	High Comfort 4000K MTR-LED asymmetrical	LVK → 8216		

Please complete the reference no. with the relevant codes for optics, light source and colour choice.

**Recommended poles**

Cylindrical Ø: 90mm galvanised steel pole, painted, with extended buried base and anti-sink plate set, CE-approval in accordance with the EU Building Products Act, supplied with 2x5x16mm<sup>2</sup> IP54 fusebox for through-wiring.

H: 3500 / 800mm	pole top Ø: 90mm	MH: 3700mm	<b>SX 011 14-</b>
H: 4000 / 800mm	pole top Ø: 90mm	MH: 4200mm	<b>SX 012 14-</b>

**How to order**

**SX 470 6 0 - 4**

<b>SATURN LED</b> Pole top luminaire <b>SX 470</b>	<b>LED 60W</b> <b>6 0</b>	<b>graphite - mica finish</b> <b>- 4</b>
--	------------------------------	---

**Colour code:** → - - + graphite - mica finish, other colours - - + colour code

