

- AVENUES AND BOULEVARDS
- MAIN ROADS
- INDUSTRIAL AREAS
- PUBLIC PARKS



DISCERA BASYS 750/400 roadway / walkway fixture with pole and brackets.

Housing made of die-cast aluminium, aluminium, stainless steel, toughened glass, stainless steel threaded inserts for regularly used fixing positions, stainless steel screws, features tool-free easy maintenance access with flush one hand operated locks, asymmetric high performance mirror optics - VARIO-OPTIC for all layouts, for planning assistance please contact se'lux, BASYS 750: Ø: 750mm, H: 165mm, BASYS 400: Ø: 400mm, H: 106mm, protection category IP66, protection class I with option class II, conical galvanised steel

pole, painted, features extended buried base and anti-sink plate set, CE-approval according to EU construction-product regulations, supplied with IP 54 fuse box 2x5x16mm² for loop in-and-out, H: 8000/1200mm, LPH: 7960/4450mm, standard colour: silver (RAL 9006) [-3].

A_w: 0,1 m², weight: 19 kg
Road/walkway fixture SX 337 ■ ■ ■ - ■
 including pole and brackets

HST	HIT-CE
150/50W → 1 4 → 7316 / 7322	150/35W* → 2 2 → 7315 / 7320
250/50W → 1 6 → 7318 / 7322	250/35W* → 2 3 → 7315 / 7320



VARIO-OPTIC
Mirror optic asymmetric




DISCERA BASYS 750 bracket mounted fitting to be combined with variety of arms, for mounting on our recommended poles.

Housing made of die-cast aluminium, aluminium, stainless steel, toughened glass, stainless steel threaded inserts for regularly used fixing positions, stainless steel screws, features tool-free easy maintenance access with flush one hand operated locks, asymmetric high performance mirror optics - VARIO-OPTIC for all layouts, for planning assistance please contact se'lux, Ø: 750mm, H: 165mm, spigot Ø: 60mm, protection category IP66, protection class I with option class II, standard colour: silver (RAL 9006) [-3].

A_w: 0,1 m², weight: 19 kg
Bracket mounted fitting SX 331 ■ ■ ■ - ■
 without bracket, without pole

HST	HIT-CE
150W → 2 6 LVK → 7316	150W → 2 7 LVK → 7315
250W → 2 8 LVK → 7318	250W → 2 9 LVK → 7315



VARIO-OPTIC
Mirror optic asymmetric

Recommended Poles

Conical galvanised steel pole, painted, features extended buried base and anti-sink plate set, CE-approval according to EU construction-product regulations, supplied with IP 54 fuse box 2x5x16mm² for loop in-and-out.

H: 7000 / 1200mm	pole top Ø: 90mm	LPH: 6950mm	SX 116 14- ■
H: 8000 / 1200mm	pole top Ø: 90mm	LPH: 7950mm	SX 117 14- ■
H: 10000 / 1500mm	pole top Ø: 90mm	LPH: 9950mm	SX 126 14- ■

Bracket

Pole top arm for spigot Ø: 60mm, of galvanised steel, painted.	
Single, pole top Ø: 90mm, L: 1200mm,	SX 97-306- ■
Double, pole top Ø: 90mm, L: 2400mm,	SX 97-310- ■

*G12 base • on request with Philips CosmoPolis (HIT-COS).
 Please complete reference no. with the relevant codes for optic, lamp and colour.

Specification example: Luminaire with Bracket and Pole

DISCERA BASYS 750 SX 337	asym., HST 150/50W	silver	
	14	- 3	SX 337 14 - 3
Bracket SX 097-306	L: 1200mm	- 3	SX 097-306- 3
Pole SX 117 14	H: 8000/1200mm	- 3	SX 117 14 - 3

Colour code: → ■ silver - 3, choice of colours - 9

Additional poles p.320 • wooden poles p.316 • accessories p.325 • colours p.328 • planning aids p.332 • optics p.315



