

- ACCESS AND MINOR ROADS
- PUBLIC PARKS
- INDUSTRIAL AREAS
- SQUARES AND PLAZAS
- PEDESTRIAN PRECINCTS



**OLIVIO SISTEMA Grande**  
**OLIVIO SISTEMA Medio**  
 Fitting with bracket for lateral pole attachment featuring custom defined arm layout on the system-pole. Housing of pressure die-cast aluminium, aluminium, stainless steel, toughened glass, painted, stainless steel screws, stainless steel threaded inserts for regularly used fixing positions, features easy maintenance access by locking-bar mechanism, the power cord is invisibly conducted through the head joint, the light can be accurately positioned by the 2-way adjustable head joint, swivel range at the arm from 20deg. to 195deg. and rotation +/- 180deg., choice of various optics, protection category

IP67, protection class I with option class II, features conical cast aluminium 70deg. arm, painted, choice of two standard designs: mounted with decorative step or straight to the pole, with IP67 cable connector for 3x1,5mm<sup>2</sup>, for attachment to custom design prepared SISTEMA poles, standard colour: metallic silver [-8].

**OLIVIO Grande**  
 Ø: 275mm, H: 344mm, A<sub>w</sub>: 0,079 m<sup>2</sup>  
 weight: 10 kg

**OLIVIO Grande SX 776** [Light Blue] [Light Blue] - [Pink]  
 Stepped arm

**OLIVIO Grande SX 777** [Light Blue] [Light Blue] - [Pink]  
 Straight arm

**OLIVIO Medio**  
 Ø: 220mm, H: 275mm, A<sub>w</sub>: 0,050 m<sup>2</sup>  
 weight: 6 kg

**OLIVIO Medio SX 778** [Light Blue] [Light Blue] - [Pink]  
 Stepped arm

**OLIVIO Medio SX 779** [Light Blue] [Light Blue] - [Pink]  
 Straight arm

**HIT-CE\***  
**OLIVIO Grande**

35W → 4 1

LVK → 7261

70W → 4 2

LVK → 7261

150W → 4 4

LVK → 7261

35W → 5 1

LVK → 7260

70W → 5 2

LVK → 7260

150W → 5 4

LVK → 7260

35W → 1 1

LVK → 7262

70W → 1 2

LVK → 7262

100W → 1 3

LVK → 7262

150W → 1 4

LVK → 7262

35W → 2 1

LVK → 7263

70W → 2 2

LVK → 7263

100W → 2 3

LVK → 7263

150W → 2 4

LVK → 7263

35W → 3 1

LVK → 7264

70W → 3 2

LVK → 7264

100W → 3 3

LVK → 7264

150W → 3 4

LVK → 7264

**HIT-CE\***  
**OLIVIO Medio**

35W → 1 1

LVK → 7267

70W → 1 2

LVK → 7267

100W → 1 3

LVK → 7267

150W → 1 4

LVK → 7267

35W → 2 0

LVK → 7268

70W → 2 2

LVK → 7268

35W → 3 1


LVK → 7269

70W → 3 2

LVK → 7269




mini-road asymmetric



mini-road symmetric





spot





medium





flood





**OLIVIO Grande SX 776**  
 Stepped arm



**OLIVIO Grande SX 777**  
 Straight arm



**OLIVIO Medio SX 778**  
 Stepped arm



**OLIVIO Medio SX 779**  
 Straight arm




\*G12 base • on request with Philips CosmoPolis (HIT-COS).  
 Please complete reference no. with the relevant codes for optics, lamp and colour.



Specification example: Fitting with system-pole


<b>OLIVIO Grande</b>	<b>asym., HIT-CE 35W</b>	<b>silver</b>	
<b>SX 776</b>	<b>4 1</b>	<b>- 8</b>	<b>SX 776 4 1 - 8</b>
<b>Pole SX 160 23</b>	<b>H: 8000/200mm</b>	<b>- 8</b>	<b>SX 160 23 - 8</b>

Colour code: → ■ metallic silver - **8**, choice of colours - **9**




+

8000



+

10000



**OLIVIO SISTEMA – System-pole**

Conical galvanised steel pole with flange plate, painted, prepared at the factory for attachment of OLIVIO SISTEMA fittings after custom attachment design, separate galvanised steel buried base with flange plate and anti-sink plate, CE-approval according to EU construction-product regulations, supplied with IP 54 fuse box 2x5x16mm<sup>2</sup> for loop in-and-out.

H: 8000 / 200mm	custom designed attachment	<b>SX 160 23-</b> <span style="color: #e91e63;">■</span>
H: 10000 / 200mm	custom designed attachment	<b>SX 161 23-</b> <span style="color: #e91e63;">■</span>

