


- STAIRWAYS AND PATHWAYS
- ENTRANCE AREAS
- PEDESTRIAN PRECINCTS



**MTR 200 Wall fitting** with bracket.

Housing made of die-cast aluminium, aluminium, stainless steel, PMMA, painted, stainless steel screws, stainless steel threaded inserts for regularly used fixing positions, MTR 200-refractor, Ø: 200mm, H: 460mm, protection category IP54, protection class I with option class II, including wall bracket of die-cast aluminium and terminal block with fuse, painted, standard colour: black [-2].



**Wall fitting** **SX 563** ■ ■ - ■

HSE		HIE-CE
70W → <span style="color: #00AEEF;">1 1</span>		70W → <span style="color: #00AEEF;">1 3</span>
LVK → 7821		LVK → 7821



MTR 200 refractor




**MTR 200 Bollard** for mounting on plinth or separate buried base.

Housing made of die-cast aluminium, aluminium, stainless steel, PMMA, painted, stainless steel screws, stainless steel threaded inserts for regularly used fixing positions, MTR 200-refractor, Ø: 200mm, H: 1350mm, protection category IP54, protection class I with option class II, column without door, painted, supplied with IP 54 fuse box 2x5x10mm<sup>2</sup> for loop in-and-out, standard colour: black [-2].

**Bollard** **SX 713** ■ ■ - ■

HSE		HIE-CE
70W → <span style="color: #00AEEF;">3 1</span>		70W → <span style="color: #00AEEF;">3 3</span>
LVK → 8004		LVK → 8004



MTR 200 refractor

Please complete reference no. with the relevant codes for optics, lamp and colour.

**Specification example:** **SX 563** 1 1 - 2 **MTR 200 Wall fitting SX 563** **HSE 70W MTR 200** 1 1 **black** - 2

**Colour code:** → ■ black - 2, choice of colours - 9

**Buried base** of galvanised steel with flange and anti-sink plate

H: 500mm, flange plate Ø: 200mm anti-sink plate □ 200mm<sup>2</sup> **SX 97-052-0**

Buried bases p.324 • accessories p.325 • colours p.328 • planning aids p.332 • optics p.315 • wall plate dimensions p.326

