



Apparecchio per applicazione a pavimento, testa inclinata, con sorgenti a led o fluorescente.

Lighting fixture for floor mounting, inclined head, with led or fluorescent source.

Equipo para aplicar en el pavimento, cabeza inclinada, con focos de LED o fluorescente.

Appareil pour l'application au sol, tête inclinée, avec sources à LED ou fluorescente.

Leuchte für Bodenmontage mit schräg stehendem Kopf, geeignet für LED-Leuchten oder Leuchtstoffbirnen.





h (m)	L (m)	I (m)	E MED (Lux)
0,35	2,5	9	20

## Stalk Mini Led



FINISH	CODE	COLOUR LED	ELECTRIFICATION
A5	58115...	...C ...N ...W	2 LED x 2 W (4W) - 120°
A6	58116...	...C ...N ...W	2 LED x 2 W (4W) - 120°
A7	58117...	...C ...N ...W	2 LED x 2 W (4W) - 120°

Weight Kg. 2,16  
Volume m³ 0,007



h (m)	L (m)	I (m)	E MED (Lux)
0,36	2,5	9	23

## Stalk Mini



FINISH	CODE	LAMP	ELECTRIFICATION
A5	57735		TC-TSE E27 max 14 W - 240V
A6	57736		TC-TSE E27 max 14 W - 240V
A7	57737		TC-TSE E27 max 14 W - 240V

Weight Kg. 2,05  
Volume m³ 0,012



### ORDER CODE COMPOSITION:

CODE	COLOUR LED	order code
58115 +	C	= 58115C

### COLOURS:

Bianco Caldo da 2800 a 3400 °K Warm-White from 2800 to 3400 °K Blanco Caliente de 2800 a 3400 °K Blanc Chaud de 2800 à 3400 °K Warmes Weiß ab 2800 bis 3400 °K	Bianco Naturale da 3700 a 4300 °K Natural-White from 3700 to 4300 °K Blanco Natural de 3700 a 4300 °K Blanc Naturel de 3700 à 4300 °K Naturales Weiß ab 3700 bis 4300 °K	Bianco Freddo da 5000 a 6000 °K Cool-White from 5000 to 6000 °K Blanco Frío de 5000 a 6000 °K Blanc Froid de 5000 à 6000 °K Kaltes Weiß ab 5000 bis 6000 °K
<b>W</b>	<b>N</b>	<b>C</b>